

屋内照明器具特性

品番 (品名)	NNN12610															
光源	LDT6L-G/S/T6 ×1				810.0 lm											
管理番号	K0163081(0)DB1															
BZ分類	BZ6															

器具効率	60%	天井	80%				70%				50%				30%				0%		
	上方光束		36%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		24%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01) ZCM																				
保守率	良	0.63	0.6	2.8	2.1	1.6	1.3	2.5	1.9	1.5	1.2	2.0	1.6	1.2	1.0	1.6	1.2	1.0	0.8	0.5	
	中	0.6	0.8	3.3	2.6	2.1	1.8	3.0	2.4	2.0	1.7	2.4	2.0	1.6	1.4	1.9	1.5	1.3	1.1	0.7	
	否	0.56	1.0	3.6	3.0	2.5	2.2	3.3	2.7	2.3	2.0	2.7	2.2	1.9	1.7	2.1	1.8	1.5	1.4	0.8	
			1.25	4.0	3.4	2.9	2.6	3.6	3.1	2.7	2.4	2.9	2.5	2.2	2.0	2.3	2.0	1.8	1.6	1.0	
下方投影面積 等価発光面積	cm ²		1.5	4.2	3.6	3.2	2.9	3.8	3.3	3.0	2.7	3.1	2.7	2.5	2.2	2.4	2.2	2.0	1.8	1.1	
	cm ²		2.0	4.5	4.0	3.7	3.4	4.1	3.7	3.4	3.1	3.3	3.0	2.8	2.6	2.6	2.4	2.2	2.1	1.3	
	器具間隔最大限		2.5	4.7	4.3	4.0	3.7	4.3	3.9	3.6	3.4	3.5	3.2	3.0	2.8	2.8	2.6	2.4	2.3	1.4	
取付高さ	Hm		3.0	4.9	4.5	4.2	3.9	4.4	4.1	3.9	3.6	3.6	3.4	3.2	3.0	2.9	2.7	2.6	2.4	1.5	
	Hm		4.0	5.1	4.8	4.5	4.3	4.6	4.4	4.1	3.9	3.8	3.6	3.4	3.3	3.0	2.9	2.8	2.6	1.7	
Hm	1.56Hm		5.0	5.2	4.9	4.7	4.5	4.7	4.5	4.3	4.1	3.9	3.7	3.6	3.5	3.1	3.0	2.9	2.8	1.8	
	1.17Hm		7.0	5.3	5.1	4.9	4.8	4.9	4.7	4.6	4.4	4.0	3.9	3.8	3.7	3.2	3.1	3.0	3.0	1.9	
			10.0	5.4	5.3	5.1	5.0	5.0	4.9	4.7	4.6	4.1	4.0	3.9	3.9	3.3	3.2	3.2	3.1	2.0	

