

屋内照明器具特性	
品番 (品名)	NNN12620
光源	LDT8L-G/Z60/S/W ×1 810.0 lm
管理番号	K0138597(0)DB1
BZ分類	BZ10/0.7/BZ9

器具効率	51%	反射率	天井	80%				70%				50%				30%				0%
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	22%	床	10%				10%				10%				10%				0%	
下方光束	29%	室指数	照明率 (X0.01)																ZCM	
保守率	良 0.63	0.6	2.2	1.5	1.1	0.8	2.0	1.4	1.0	0.8	1.7	1.2	0.9	0.6	1.4	1.0	0.7	0.5	0.2	
	中 0.6	0.8	2.6	2.0	1.5	1.2	2.4	1.8	1.4	1.1	2.0	1.5	1.2	0.9	1.6	1.2	1.0	0.8	0.4	
	否 0.56	1.0	3.0	2.3	1.8	1.5	2.7	2.1	1.7	1.4	2.2	1.8	1.4	1.2	1.8	1.5	1.2	1.0	0.6	
		1.25	3.2	2.6	2.2	1.8	3.0	2.4	2.0	1.7	2.5	2.0	1.7	1.4	2.0	1.7	1.4	1.2	0.8	
下方投影面積	cm <sup>2</sup>	1.5	3.5	2.9	2.4	2.1	3.2	2.7	2.3	1.9	2.6	2.2	1.9	1.7	2.2	1.9	1.6	1.4	0.9	
等価発光面積		2.0	3.8	3.3	2.8	2.5	3.5	3.0	2.6	2.3	2.9	2.5	2.3	2.0	2.4	2.1	1.9	1.7	1.1	
取付高さ	器具間隔最大限		2.5	3.9	3.5	3.1	2.8	3.6	3.2	2.9	2.6	3.1	2.8	2.5	2.2	2.5	2.3	2.1	1.9	1.3
	横方向 (A)	縦方向 (B)	3.0	4.1	3.7	3.3	3.0	3.8	3.4	3.1	2.8	3.2	2.9	2.7	2.4	2.7	2.4	2.2	2.1	1.4
H <sub>m</sub>	1.46H <sub>m</sub>	2.57H <sub>m</sub>	4.0	4.3	3.9	3.7	3.4	4.0	3.7	3.4	3.2	3.4	3.1	2.9	2.7	2.8	2.6	2.5	2.3	1.7
			5.0	4.4	4.1	3.9	3.6	4.1	3.8	3.6	3.4	3.5	3.3	3.1	2.9	2.9	2.8	2.6	2.5	1.8
			7.0	4.6	4.3	4.1	3.9	4.2	4.0	3.9	3.7	3.7	3.5	3.3	3.2	3.1	3.0	2.8	2.7	2.0
			10.0	4.7	4.5	4.3	4.2	4.4	4.2	4.1	3.9	3.8	3.6	3.5	3.4	3.2	3.1	3.0	2.9	2.2

