

屋内照明器具特性

品番 (品名)	NNN12622														
光源	LDT6L-G/S/T6 ×1 810.0 lm														
管理番号	K0163285(1)DB1														
BZ分類	BZ3														

器具効率	22%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	11%	反射率	10%				10%				10%				10%				0%	
下方光束	11%		床	10%				10%				10%				10%				0%
		室指数	照明率 (X0.01)															ZCM		
保守率	良	0.63	0.6	12	9	8	7	11	9	7	6	9	7	6	6	8	6	6	5	4
	中	0.6	0.8	14	11	10	9	12	11	9	8	11	9	8	7	9	8	7	6	5
	否	0.56	1.0	15	13	11	10	14	12	11	10	12	10	9	9	10	9	8	7	6
			1.25	16	14	13	12	15	13	12	11	13	11	10	10	11	10	9	8	6
下方投影面積		cm ²	1.5	17	15	14	13	16	14	13	12	13	12	11	11	11	10	10	9	7
等価発光面積		cm ²	2.0	18	17	15	14	17	15	14	14	14	13	13	12	12	11	11	10	8
取付高さ	器具間隔最大限		2.5	19	17	16	16	17	16	15	15	15	14	13	13	12	12	11	11	8
	横方向 (A)	縦方向 (B)	3.0	19	18	17	16	18	17	16	15	15	14	14	13	13	12	12	11	9
H _m	1.04H _m	1.16H _m	4.0	20	19	18	18	18	18	17	16	16	15	15	14	13	13	12	12	9
			5.0	20	19	19	18	19	18	18	17	16	15	15	15	13	13	13	12	9
			7.0	20	20	19	19	19	19	18	18	16	16	16	15	14	13	13	13	10
			10.0	21	20	20	20	19	19	19	18	16	16	16	16	14	14	14	13	10

