

| | |
|----------|-----------------------------|
| 屋内照明器具特性 | |
| 品番 (品名) | NNN12622 |
| 光源 | LDT8L-G/Z60/S/W ×1 810.0 lm |
| 管理番号 | K0138593(0)DB1 |
| BZ分類 | BZ3 |

| | | | | | | | | | | | | | | | | | | | |
|--------|-----------------|---------|---------------|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|----|----|-----|
| 器具効率 | 23% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% |
| | | 壁 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% |
| 上方光束 | 13% | 床 | 10% | | | | 10% | | | | 10% | | | | 10% | | | | 0% |
| 下方光束 | 10% | 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | ZCM |
| 保守率 | 良 0.63 | 0.6 | 12 | 9 | 8 | 7 | 11 | 9 | 7 | 6 | 9 | 7 | 6 | 6 | 7 | 6 | 5 | 5 | 4 |
| | 中 0.6 | 0.8 | 13 | 11 | 10 | 9 | 12 | 11 | 9 | 8 | 10 | 9 | 8 | 7 | 9 | 8 | 7 | 6 | 5 |
| | 否 0.56 | 1.0 | 15 | 13 | 11 | 10 | 14 | 12 | 11 | 10 | 12 | 10 | 9 | 8 | 10 | 9 | 8 | 7 | 5 |
| | | 1.25 | 16 | 14 | 13 | 12 | 15 | 13 | 12 | 11 | 12 | 11 | 10 | 10 | 10 | 9 | 9 | 8 | 6 |
| 下方投影面積 | cm ² | 1.5 | 17 | 15 | 14 | 13 | 16 | 14 | 13 | 12 | 13 | 12 | 11 | 10 | 11 | 10 | 9 | 7 | |
| 等価発光面積 | | 2.0 | 18 | 17 | 15 | 14 | 17 | 15 | 14 | 14 | 14 | 13 | 12 | 12 | 12 | 11 | 10 | 7 | |
| 取付高さ | 器具間隔最大限 | | 2.5 | 19 | 17 | 16 | 16 | 17 | 16 | 15 | 15 | 14 | 14 | 13 | 13 | 12 | 11 | 11 | 8 |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 19 | 18 | 17 | 16 | 18 | 17 | 16 | 15 | 15 | 14 | 14 | 13 | 12 | 12 | 11 | 8 |
| Hm | 1.03Hm | 1.20Hm | 4.0 | 20 | 19 | 18 | 17 | 18 | 17 | 17 | 16 | 15 | 15 | 14 | 14 | 13 | 12 | 12 | 9 |
| | | | 5.0 | 20 | 19 | 19 | 18 | 19 | 18 | 17 | 17 | 16 | 15 | 15 | 15 | 13 | 13 | 12 | 9 |
| | | | 7.0 | 20 | 20 | 19 | 19 | 19 | 18 | 18 | 18 | 16 | 16 | 15 | 15 | 13 | 13 | 13 | 9 |
| | | | 10.0 | 21 | 20 | 20 | 20 | 19 | 19 | 19 | 18 | 16 | 16 | 16 | 16 | 13 | 13 | 13 | 9 |

