

# 屋内照明器具特性

品番 (品名)	NNN13600B	
光源	LDA8L - H/ E/ W ×1	810.0 lm
管理番号	K0177557 (0) DB 1	
BZ分類	BZ2	

器具効率	48%	天井	80%				70%				50%				30%				0%		
	上方光束		0%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		48%		床	10%				10%				10%				10%			
室指数	照明率 ( X0.01 )																				ZCM
保守率	良	0.63	0.6	3.2	2.8	2.5	2.3	3.2	2.7	2.5	2.3	3.1	2.7	2.4	2.2	3.0	2.7	2.4	2.2	2.2	
	中	0.6	0.8	3.7	3.3	3.0	2.8	3.7	3.3	3.0	2.8	3.6	3.2	3.0	2.8	3.5	3.2	2.9	2.8	2.7	
	否	0.56	1.0	4.0	3.7	3.4	3.2	4.0	3.6	3.4	3.2	3.8	3.6	3.3	3.2	3.7	3.5	3.3	3.1	3.0	
			1.25	4.3	3.9	3.7	3.5	4.2	3.9	3.7	3.5	4.1	3.8	3.6	3.5	4.0	3.8	3.6	3.4	3.4	
下方投影面積	cm <sup>2</sup>		1.5	4.4	4.1	3.9	3.7	4.4	4.1	3.9	3.7	4.2	4.0	3.8	3.7	4.1	3.9	3.8	3.7	3.6	
	等価発光面積		cm <sup>2</sup>	2.0	4.6	4.4	4.2	4.0	4.6	4.3	4.2	4.0	4.4	4.3	4.1	4.0	4.3	4.2	4.0	3.9	3.8
取付高さ	器具間隔最大限		2.5	4.7	4.6	4.4	4.2	4.7	4.5	4.4	4.2	4.6	4.4	4.3	4.2	4.5	4.3	4.2	4.1	4.0	
	横方向 (A)	縦方向 (B)	3.0	4.8	4.7	4.5	4.4	4.8	4.6	4.5	4.4	4.6	4.5	4.4	4.3	4.5	4.4	4.3	4.2	4.1	
Hm	1.07Hm	1.26Hm	4.0	4.9	4.8	4.7	4.6	4.9	4.7	4.6	4.5	4.7	4.6	4.6	4.5	4.6	4.5	4.5	4.4	4.3	
			5.0	5.0	4.9	4.8	4.7	4.9	4.8	4.7	4.7	4.8	4.7	4.6	4.6	4.7	4.6	4.6	4.5	4.4	
			7.0	5.1	5.0	4.9	4.8	5.0	4.9	4.9	4.8	4.9	4.8	4.8	4.7	4.8	4.7	4.7	4.6	4.5	
			10.0	5.1	5.0	5.0	4.9	5.0	5.0	4.9	4.9	4.9	4.9	4.8	4.8	4.8	4.8	4.7	4.7	4.6	

