

# 屋内照明器具特性

|         |                    |          |
|---------|--------------------|----------|
| 品番 (品名) | NTS32733S+NTS92101 |          |
| 光源      | LED3000_70_380 ×1  | 380.0 lm |
| 管理番号    | K0155952(9)DJ1     |          |
| BZ分類    | BZ1                |          |

| 器具効率             | 101%            | 天井      | 80%         |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0%  |    |
|------------------|-----------------|---------|-------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|
|                  |                 |         | 70          | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  |     |    |
| 上方光束             | 0%              | 反射率     | 壁           | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 0% |
| 下方光束             | 101%            |         | 床           | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 0% |
|                  |                 | 室指数     | 照明率 (X0.01) |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     | ZCM |    |
| 保守率              | 良 0.67          | 0.6     | 91          | 86  | 83  | 81  | 90  | 86  | 83  | 81  | 89  | 85  | 83  | 81  | 88  | 85  | 82  | 81  | 80  |    |
|                  | 中 0.63          | 0.8     | 95          | 91  | 88  | 86  | 95  | 91  | 88  | 86  | 93  | 90  | 88  | 86  | 92  | 89  | 87  | 86  | 85  |    |
|                  | 否 0.56          | 1.0     | 98          | 94  | 92  | 90  | 97  | 94  | 91  | 89  | 96  | 93  | 91  | 89  | 95  | 92  | 90  | 89  | 88  |    |
| 下方投影面積<br>等価発光面積 | cm <sup>2</sup> | 1.25    | 100         | 97  | 95  | 93  | 99  | 96  | 94  | 92  | 98  | 95  | 93  | 92  | 96  | 94  | 93  | 91  | 90  |    |
|                  |                 | 1.5     | 102         | 99  | 96  | 95  | 101 | 98  | 96  | 94  | 99  | 97  | 95  | 94  | 98  | 96  | 94  | 93  | 92  |    |
|                  |                 | 2.0     | 103         | 101 | 99  | 98  | 102 | 100 | 99  | 97  | 101 | 99  | 97  | 96  | 99  | 98  | 96  | 95  | 94  |    |
| 取付高さ             | 器具間隔最大限         |         | 2.5         | 104 | 102 | 101 | 99  | 104 | 102 | 100 | 99  | 102 | 100 | 99  | 98  | 100 | 99  | 98  | 97  | 95 |
|                  | 横方向 (A)         | 縦方向 (B) | 3.0         | 105 | 103 | 102 | 101 | 104 | 103 | 101 | 100 | 102 | 101 | 100 | 99  | 101 | 100 | 99  | 98  | 96 |
| Hm               | 0.47Hm          | 0.47Hm  | 4.0         | 106 | 105 | 104 | 102 | 105 | 104 | 103 | 102 | 103 | 102 | 101 | 100 | 101 | 100 | 100 | 99  | 97 |
|                  |                 |         | 5.0         | 107 | 106 | 105 | 104 | 106 | 105 | 104 | 103 | 104 | 103 | 102 | 101 | 102 | 101 | 100 | 100 | 98 |
|                  |                 |         | 7.0         | 107 | 106 | 106 | 105 | 106 | 105 | 105 | 104 | 104 | 104 | 103 | 102 | 102 | 102 | 101 | 101 | 98 |
|                  |                 |         | 10.0        | 108 | 107 | 107 | 106 | 107 | 106 | 106 | 105 | 104 | 104 | 104 | 103 | 102 | 102 | 102 | 101 | 99 |

