

屋内照明器具特性

品番 (品名)	NTS32834S+NTS92201	
光源	LED2700_70_680 ×1	680.0 l m
管理番号	K0155952(9)DJ1	
BZ分類	BZ1	

器具効率	101%	天井	80%				70%				50%				30%				0%	
	上方光束 0%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	101%	床		10%				10%				10%				10%				0%
室指数	照明率 (X0.01)																ZCM			
保守率	良 0.67	0.6	91	86	83	81	90	86	83	81	89	85	83	81	88	85	82	81	80	
	中 0.63		0.8	95	91	88	86	95	91	88	86	93	90	88	86	92	89	87	86	85
	否 0.56		1.0	98	94	92	90	97	94	91	89	96	93	91	89	95	92	90	89	88
下方投影面積 等価発光面積	cm ²	1.25	100	97	95	93	99	96	94	92	98	95	93	92	96	94	93	91	90	
		1.5	102	99	96	95	101	98	96	94	99	97	95	94	98	96	94	93	92	
		2.0	103	101	99	98	102	100	99	97	101	99	97	96	99	98	96	95	94	
取付高さ	器具間隔最大限		2.5	104	102	101	99	104	102	100	99	102	100	99	98	100	99	98	97	95
	横方向 (A)	縦方向 (B)	3.0	105	103	102	101	104	103	101	100	102	101	100	99	101	100	99	98	96
Hm	0.47Hm	0.47Hm	4.0	106	105	104	102	105	104	103	102	103	102	101	100	101	100	100	99	97
			5.0	107	106	105	104	106	105	104	103	104	103	102	101	102	101	100	100	98
			7.0	107	106	106	105	106	105	105	104	104	104	103	102	102	102	101	101	98
			10.0	108	107	107	106	107	106	106	105	104	104	104	103	102	102	102	101	99

