

屋内照明器具特性	
品番 (品名)	L G S 1 0 0 5 L
光源	LDA7L - G - E17 / E / S / W ×1 760.0 l m
管理番号	K0172633 (0) DB 1
B Z 分類	BZ6 / 0.7 / BZ5

器具効率		85 %	反射率	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
				床	10 %				10 %				10 %				10 %				0 %		
上方光束		18 %	室指数	照明率 (X0.01)																	Z	C	M
下方光束		67 %																					
保守率		良 中 否	0.67	0.6	44	34	27	23	42	33	26	22	38	30	25	21	35	28	23	20	17		
			0.63	0.8	52	43	36	31	50	41	35	30	46	38	33	29	42	35	31	27	24		
			0.56	1.0	58	49	42	37	55	47	41	36	50	43	38	34	46	40	36	32	28		
				1.25	63	54	48	43	60	52	46	42	55	49	44	40	50	45	41	37	33		
下方投影面積		c m ²		1.5	66	58	52	47	63	56	51	46	58	52	48	44	53	48	44	41	36		
等価発光面積			c m ²	2.0	71	64	59	54	68	62	57	53	62	57	53	50	57	53	50	47	42		
取付高さ	器具間隔最大限			2.5	74	68	63	59	71	66	61	57	65	61	57	54	60	56	53	51	45		
				3.0	76	71	66	63	73	68	64	61	67	63	60	57	62	59	56	54	48		
H m	1.54 H m	1.54 H m		4.0	79	75	71	67	76	72	68	65	70	67	64	61	64	62	60	58	51		
				5.0	80	77	74	71	77	74	71	69	72	69	66	64	66	64	62	60	54		
				7.0	82	80	77	75	79	77	75	72	74	72	70	68	68	66	65	63	57		
				10.0	84	82	80	78	81	79	77	76	75	74	72	71	70	68	67	66	59		

