

屋内照明器具特性

品番 (品名)	NNQ35531														
光源	LED2700_85_3215 x1 3215.0 lm														
管理番号	K0160633(0)DB1														
BZ分類	BZ1														

器具効率	101%	天井	80%				70%				50%				30%				0%
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10
上方光束	0%	反射率	10%				10%				10%				10%				0%
下方光束	101%		床	10%				10%				10%				10%			
		室指数	照明率 (X0.01) ZCM																
保守率	良 中 否 0.81 0.77 0.68	0.6	74	66	61	57	73	65	60	57	72	65	60	57	70	64	60	56	55
		0.8	83	75	70	67	82	75	70	66	80	74	69	66	78	73	69	66	64
		1.0	88	81	76	73	87	81	76	73	85	79	75	72	83	78	75	72	70
		1.25	92	86	82	78	91	86	81	78	89	84	81	78	87	83	80	77	76
下方投影面積	c m ²	1.5	95	90	86	82	94	89	85	82	91	87	84	81	89	86	83	81	79
		2.0	98	94	91	88	97	93	90	87	95	92	89	86	93	90	88	86	84
取付高さ	器具間隔最大限		2.5	100	97	94	91	99	96	93	91	97	94	92	90	95	93	91	89
	横方向 (A)	縦方向 (B)	3.0	102	99	96	94	101	98	95	93	98	96	94	92	96	94	92	91
H m	1.12 H m	1.12 H m	4.0	104	101	99	97	102	100	98	96	100	98	97	95	98	96	95	94
			5.0	105	103	101	99	103	102	100	99	101	100	98	97	99	98	97	96
			7.0	106	104	103	102	105	103	102	101	102	101	100	99	100	99	98	95
			10.0	107	106	105	104	106	105	104	103	103	103	102	101	101	100	100	99

