

# 屋内照明器具特性

品番 (品名)	NNN1 2 2 6 0														
光源	LDA8L-D-G-E17/S/Z6 ×1 760.0 1 m														
管理番号	K0172973 ( 0 ) DR 1														
BZ分類	BZ7														

器具効率	85 %	天井	80 %				70 %				50 %				30 %				0 %		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束	54 %	室指数	照明率 ( X0.01 )																ZCM		
下方光束	31 %																				
保守率	良 中 否 0.63 0.6 0.56	0.6	3.8	2.8	2.2	1.8	3.5	2.6	2.0	1.6	2.7	2.1	1.6	1.3	2.1	1.6	1.3	1.0	0.5		
		0.8	4.5	3.6	2.9	2.4	4.1	3.2	2.7	2.2	3.2	2.6	2.2	1.8	2.5	2.0	1.7	1.4	0.7		
		1.0	5.0	4.1	3.5	3.0	4.5	3.7	3.1	2.7	3.6	3.0	2.6	2.2	2.7	2.3	2.0	1.7	0.9		
		1.25	5.5	4.6	4.0	3.5	4.9	4.2	3.6	3.2	3.9	3.4	3.0	2.6	3.0	2.6	2.3	2.0	1.1		
下方投影面積 等価発光面積	c m <sup>2</sup>	1.5	5.8	5.0	4.4	3.9	5.2	4.6	4.0	3.6	4.2	3.7	3.3	2.9	3.2	2.8	2.5	2.3	1.3		
		2.0	6.3	5.6	5.0	4.6	5.7	5.1	4.6	4.2	4.5	4.1	3.7	3.4	3.5	3.2	2.9	2.7	1.5		
		2.5	6.6	6.0	5.5	5.0	5.9	5.4	5.0	4.6	4.8	4.4	4.1	3.8	3.7	3.4	3.1	2.9	1.7		
取付 高さ	器具間隔最大限		3.0	6.8	6.2	5.8	5.4	6.1	5.7	5.3	4.9	4.9	4.6	4.3	4.0	3.8	3.6	3.3	3.1	1.8	
	横方向 (A)	縦方向 (B)																			
1.5m	2.52 m	2 m	4.0	7.0	6.6	6.2	5.9	6.4	6.0	5.7	5.4	5.2	4.9	4.6	4.4	4.0	3.8	3.6	3.4	2.0	
2	3.36	2.67	5.0	7.2	6.8	6.5	6.2	6.6	6.2	5.9	5.7	5.3	5.1	4.8	4.6	4.1	4.0	3.8	3.6	2.2	
2.5	4.2	3.34	7.0	7.4	7.1	6.9	6.6	6.8	6.5	6.3	6.1	5.5	5.3	5.1	5.0	4.3	4.1	4.0	3.9	2.3	
3	5.04	4	10.0	7.6	7.4	7.2	7.0	6.9	6.7	6.6	6.4	5.6	5.5	5.4	5.2	4.4	4.3	4.2	4.1	2.5	

