

屋内照明器具特性

品番 (品名)	NNN13208															
光源	LED3000_70_1255 x1 1255.0 1 m															
管理番号	K0167811(0)DR1															
BZ分類	BZ7/0.7/BZ6															

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
		床	10 %				10 %				10 %				10 %				0 %	
上方光束	43 %																			
下方光束	57 %																			
室指数	照明率 (X0.01) ZCM																			
保守率	良 中 否	0.63	0.6	48	35	28	22	44	33	26	21	37	29	23	18	31	24	20	16	11
		0.6	0.8	56	44	36	30	52	41	34	29	44	36	30	25	37	31	26	22	16
			1.0	62	51	43	37	58	47	40	35	49	41	35	30	41	35	30	26	19
		0.56	1.25	68	57	49	43	63	53	46	41	53	46	40	36	45	39	35	31	23
下方投影面積	c m ²	1.5	72	62	54	48	66	58	51	46	57	50	45	40	48	43	38	35	26	
		2.0	77	69	62	56	72	64	58	53	61	56	51	47	52	47	44	40	30	
取付高さ	器具間隔最大限		2.5	81	73	67	62	75	69	63	58	65	59	55	51	55	51	47	44	33
	横方向 (A)	縦方向 (B)	3.0	83	77	71	66	78	72	67	62	67	62	58	55	57	53	50	47	36
1.5m	1.96 m	1.92 m	4.0	87	81	76	72	81	76	72	68	70	66	63	60	60	57	54	52	39
2	2.61	2.53	5.0	89	84	80	76	83	79	75	72	72	69	66	63	61	59	57	54	42
2.5	3.26	3.14	7.0	91	88	84	81	85	82	79	76	74	72	69	67	64	62	60	58	45
3	3.9	3.75	10.0	93	91	88	86	87	85	83	81	76	74	73	71	66	64	63	61	47

