

屋内照明器具特性

品番 (品名)	NNY20512K														
光源	LED5000_85_21000 ×1 21000.0 1 m														
管理番号	K0143898 (0) DR 1														
BZ分類	BZ4														

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束	2 %	室指数	照明率 (X0.01)																ZCM		
下方光束	98 %																				
保守率	良 中 否 0.83 0.81 0.77	0.6	58	47	39	34	57	46	39	34	55	45	38	34	52	44	38	33	31		
		0.8	69	58	50	45	67	57	50	44	64	55	49	44	62	54	48	44	42		
		1.0	75	65	58	52	74	64	57	52	71	62	56	52	68	61	55	51	49		
		1.25	81	72	65	60	79	71	65	60	76	69	64	59	73	67	62	58	56		
下方投影面積	c m ²	1.5	85	77	71	66	83	76	70	65	80	74	69	64	77	72	67	64	61		
		2.0	91	84	78	74	89	83	77	73	86	80	76	72	83	78	74	71	68		
取付高さ	器具間隔最大限		2.5	94	88	83	79	92	87	82	79	89	85	81	77	86	82	79	76	73	
	横方向 (A)	縦方向 (B)	3.0	96	91	87	83	95	90	86	82	91	88	84	81	89	85	82	80	77	
H m	1.25 H m	1.25 H m	4.0	99	95	92	89	98	94	91	88	94	91	89	86	92	89	87	85	82	
			5.0	101	98	95	92	99	96	94	91	96	94	91	89	93	91	89	88	85	
			7.0	103	100	98	96	101	99	97	95	98	97	95	93	96	94	93	91	88	
			10.0	104	103	101	99	103	101	100	98	100	99	97	96	97	96	95	94	91	

