

屋内照明器具特性	
品番 (品名)	L G W C 8 5 0 7 4 U
光源	L D A 4 L - H - E 1 7 / E / S / W / 2 × 1 4 4 0 . 0 l m
管理番号	K 0 1 2 5 8 0 3 (1) D B 1
B Z 分類	B Z 9

器具効率		3 7 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %				
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
上方光束		1 6 %	室指数	照明率 (X 0 . 0 1) Z C M																					
下方光束		2 1 %																							
保守率		良 中 否	0 . 6 3	0 . 6	1 6	1 1	8	6	1 4	1 0	7	5	1 2	9	6	5	1 0	7	5	4	2				
			0 . 6	0 . 8	1 9	1 4	1 1	8	1 7	1 3	1 0	8	1 4	1 1	8	7	1 2	9	7	5	3				
			0 . 5 6	1 . 0	2 1	1 6	1 3	1 1	1 9	1 5	1 2	1 0	1 6	1 3	1 0	8	1 3	1 0	8	7	4				
				1 . 2 5	2 3	1 9	1 5	1 3	2 1	1 7	1 4	1 2	1 8	1 5	1 2	1 0	1 4	1 2	1 0	8	5				
下方投影面積		c m ²	1 . 5	2 5	2 0	1 7	1 5	2 3	1 9	1 6	1 4	1 9	1 6	1 4	1 2	1 5	1 3	1 1	1 0	6					
等価発光面積			c m ²	2 . 0	2 7	2 3	2 0	1 8	2 5	2 1	1 9	1 7	2 1	1 8	1 6	1 4	1 7	1 5	1 3	1 2	8				
取付高さ	器具間隔最大限		2 . 5	2 8	2 5	2 2	2 0	2 6	2 3	2 1	1 9	2 2	2 0	1 8	1 6	1 8	1 6	1 5	1 4	9					
	横方向 (A) 縦方向 (B)		3 . 0	2 9	2 6	2 4	2 2	2 7	2 4	2 2	2 0	2 3	2 1	1 9	1 7	1 9	1 7	1 6	1 5	1 0					
H m	0 . 0 0 H m	1 . 4 5 H m	4 . 0	3 0	2 8	2 6	2 4	2 8	2 6	2 4	2 3	2 4	2 2	2 1	1 9	2 0	1 9	1 8	1 7	1 2					
			5 . 0	3 1	2 9	2 7	2 6	2 9	2 7	2 6	2 4	2 5	2 4	2 2	2 1	2 1	2 0	1 9	1 8	1 3					
			7 . 0	3 2	3 1	2 9	2 8	3 0	2 9	2 7	2 6	2 6	2 5	2 4	2 3	2 2	2 1	2 0	1 9	1 4					
			1 0 . 0	3 3	3 2	3 1	3 0	3 1	3 0	2 9	2 8	2 7	2 6	2 5	2 4	2 3	2 2	2 2	2 1	1 6					

