

屋内照明器具特性	
品番 (品名)	L G W C 8 5 0 8 2 Z
光源	L D A 4 L - H - E 1 7 / E / S / W / 2 × 1 4 4 0 . 0 l m
管理番号	K 0 1 7 2 6 6 1 (0) D R 1
B Z 分類	B Z 8

器具効率		63 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.63	0.6	2.9	2.0	1.5	1.2	2.6	1.9	1.4	1.1	2.3	1.7	1.3	1.0	1.9	1.4	1.1	0.8	0.6
			0.6	0.8	3.4	2.6	2.1	1.7	3.1	2.4	1.9	1.6	2.7	2.1	1.7	1.4	2.3	1.8	1.5	1.2	0.8
			0.56	1.0	3.8	3.0	2.4	2.0	3.5	2.8	2.3	1.9	3.0	2.4	2.0	1.7	2.5	2.1	1.7	1.5	1.1
				1.25	4.1	3.4	2.9	2.4	3.8	3.2	2.7	2.3	3.3	2.8	2.4	2.0	2.8	2.4	2.0	1.8	1.3
下方投影面積		cm ²		1.5	4.4	3.7	3.2	2.8	4.1	3.5	3.0	2.6	3.5	3.0	2.6	2.3	3.0	2.6	2.3	2.0	1.5
			等価発光面積	cm ²	2.0	4.7	4.1	3.7	3.3	4.4	3.9	3.4	3.1	3.8	3.4	3.0	2.7	3.2	2.9	2.6	2.4
取付高さ	器具間隔最大限			2.5	5.0	4.4	4.0	3.6	4.6	4.2	3.8	3.4	4.0	3.6	3.3	3.0	3.4	3.1	2.9	2.7	2.0
	横方向 (A)		縦方向 (B)	3.0	5.1	4.7	4.3	3.9	4.8	4.4	4.0	3.7	4.2	3.8	3.5	3.3	3.6	3.3	3.1	2.9	2.2
H _m	1.49 H _m		1.57 H _m	4.0	5.4	5.0	4.6	4.3	5.0	4.7	4.4	4.1	4.4	4.1	3.8	3.6	3.8	3.6	3.4	3.2	2.5
				5.0	5.5	5.2	4.9	4.6	5.2	4.9	4.6	4.3	4.5	4.3	4.1	3.9	3.9	3.7	3.5	3.4	2.6
				7.0	5.7	5.4	5.2	4.9	5.3	5.1	4.9	4.7	4.7	4.5	4.3	4.2	4.1	3.9	3.8	3.7	2.9
				10.0	5.8	5.6	5.4	5.2	5.5	5.3	5.1	5.0	4.8	4.7	4.6	4.4	4.2	4.1	4.0	3.9	3.1

