

屋内照明器具特性	
品番 (品名)	L G W C 8 5 2 0 3 W K
光源	L D A 3 L - E 1 7 / C / W × 1 2 8 0 . 0 l m
管理番号	K 0 1 3 3 0 8 5 (0) D B 1
B Z 分類	B Z 4 / 0 . 7 / B Z 5

器具効率		8 6 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %				
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
上方光束		1 8 %	室指数	照明率 (X 0 . 0 1) Z C M																					
下方光束		6 8 %																							
保守率		良 中 否	0 . 6 7	0 . 6	4 8	3 8	3 2	2 7	4 6	3 7	3 1	2 7	4 2	3 4	2 9	2 5	3 9	3 2	2 8	2 4	2 2				
			0 . 6 3	0 . 8	5 5	4 5	3 9	3 4	5 3	4 4	3 8	3 3	4 8	4 1	3 6	3 2	4 4	3 8	3 4	3 0	2 7				
			0 . 5 6	1 . 0	6 0	5 1	4 4	3 9	5 7	4 9	4 3	3 8	5 2	4 6	4 0	3 6	4 8	4 2	3 8	3 5	3 1				
				1 . 2 5	6 5	5 6	5 0	4 5	6 2	5 4	4 8	4 4	5 7	5 0	4 6	4 2	5 2	4 7	4 3	3 9	3 5				
下方投影面積		c m ²	1 . 5	6 8	6 0	5 4	4 9	6 5	5 8	5 3	4 8	6 0	5 4	4 9	4 6	5 5	5 0	4 6	4 3	3 8					
等価発光面積			c m ²	2 . 0	7 3	6 6	6 1	5 6	7 0	6 4	5 9	5 5	6 4	5 9	5 5	5 2	5 9	5 5	5 2	4 9	4 3				
取付高さ	器具間隔最大限		2 . 5	7 6	7 0	6 5	6 1	7 3	6 7	6 3	5 9	6 7	6 3	5 9	5 6	6 1	5 8	5 5	5 2	4 7					
	横方向 (A) 縦方向 (B)		3 . 0	7 8	7 3	6 8	6 4	7 5	7 0	6 6	6 3	6 9	6 5	6 2	5 9	6 3	6 0	5 8	5 5	4 9					
H m	1 . 3 1 H m	1 . 2 8 H m	4 . 0	8 0	7 6	7 3	6 9	7 7	7 4	7 0	6 7	7 1	6 8	6 6	6 3	6 6	6 3	6 1	5 9	5 3					
			5 . 0	8 2	7 9	7 5	7 3	7 9	7 6	7 3	7 0	7 3	7 0	6 8	6 6	6 7	6 5	6 4	6 2	5 5					
			7 . 0	8 4	8 1	7 9	7 7	8 1	7 8	7 6	7 4	7 5	7 3	7 1	7 0	6 9	6 8	6 6	6 5	5 8					
			1 0 . 0	8 5	8 4	8 2	8 0	8 2	8 1	7 9	7 7	7 7	7 5	7 4	7 2	7 1	7 0	6 9	6 8	6 1					

