

屋内照明器具特性

品番 (品名)	NNQ35553														
光源	LED2700_85_4095 x1 4095.0 lm														
管理番号	K0160536(0)DB1														
BZ分類	BZ1														

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	0%	反射率	10%				10%				10%				10%				0%	
下方光束	100%		床	10%				10%				10%				10%				0%
		室指数	照明率 (X0.01) ZCM																	
保守率	良 中 否	0.81	0.6	74	66	60	57	73	65	60	57	71	65	60	57	70	64	60	56	55
		0.77	0.8	83	75	70	66	81	75	70	66	80	74	69	66	78	73	69	66	64
			1.0	88	81	76	73	87	80	76	73	85	79	75	72	83	78	75	72	70
		0.68	1.25	92	86	82	78	91	85	81	78	89	84	80	78	87	83	80	77	75
下方投影面積	c m ²	1.5	95	89	85	82	93	89	85	82	91	87	84	81	89	86	83	81	79	
		2.0	98	94	90	87	97	93	90	87	95	91	89	86	93	90	87	85	83	
等価発光面積	c m ²	2.5	100	97	94	91	99	96	93	90	97	94	92	89	95	92	90	88	86	
		3.0	102	98	96	94	100	98	95	93	98	96	94	92	96	94	92	91	88	
取付高さ	器具間隔最大限		4.0	103	101	99	97	102	100	98	96	100	98	96	95	98	96	95	94	91
	横方向 (A)	縦方向 (B)	5.0	104	102	101	99	103	101	100	98	101	99	98	97	99	98	96	95	93
H m	1.12 H m	1.12 H m	7.0	106	104	103	102	104	103	102	101	102	101	100	99	100	99	98	97	95
			10.0	106	105	104	104	105	104	103	103	103	102	101	101	100	100	99	99	96

