




非常用照明器具特性



品番	NNCF42735J (WALL)		
名称			
光源	LED5000/97/435		
管理番号	K0185274(0)DB1		
光束	870lm x 1.00		
保守率	0.92		
適用品番	設計照度Eを得るための読取照度		
	E = 2.0	E = 1.0	E = 0.5
NNCF42735J (WALL)	2.5	1.2	0.6
備考	非常点灯時の照度 (60分後)		



品番	NNCF42735J (WALL)			
名称				
光源	LED5000 / 97 / 435			
管理番号	K0185274 (0) DB 1			
光束	870.0 l m * 1.00		備考	非常点灯時の照度 (60分後)
保守率	0.92			

非常灯配置表

器具取付高さ (m)																
単体配置																
直線配置																
四角配置																
壁からの距離 (最大)																

器具取付高さ (m)																
単体配置																
直線配置																
四角配置																
壁からの距離 (最大)																

器具取付高さ (m)																
単体配置																
直線配置																
四角配置																
壁からの距離 (最大)																

階段配置表

器具取付高さ (m)			1 . 0	1 . 5	2 . 0	2 . 5	3 . 0	4 . 0	5 . 0	6 . 0	7 . 0	8 . 0
Y= 1 . 0 (m)	2 . 0 L x	X+	5 . 4	6 . 4	7 . 1	7 . 8	8 . 4	9 . 1	9 . 2	9 . 0	0 . 3	0 . 1
		X-	0 . 1	0 . 1	0 . 1	0 . 1	0 . 3	0 . 2	0 . 2	0 . 2	0 . 2	0 . 0
	1 . 0 L x	X+	6 . 7	8 . 0	9 . 0	9 . 9	10 . 6	11 . 8	12 . 5	13 . 0	13 . 1	13 . 0
Y= 1 . 5 (m)	2 . 0 L x	X+	5 . 2	6 . 3	7 . 2	7 . 9	8 . 4	9 . 0	9 . 2	9 . 1	0 . 3	0 . 1
		X-	0 . 1	0 . 1	0 . 2	0 . 3	0 . 2	0 . 2	0 . 2	0 . 2	0 . 2	0 . 0
	1 . 0 L x	X+	6 . 7	7 . 9	8 . 9	9 . 7	10 . 5	11 . 7	12 . 5	13 . 0	13 . 1	13 . 0
Y= 2 . 0 (m)	2 . 0 L x	X+	4 . 6	5 . 8	6 . 8	7 . 7	8 . 3	9 . 0	9 . 1	8 . 6	0 . 3	0 . 1
		X-	0 . 1	0 . 1	0 . 1	0 . 2	0 . 3	0 . 3	0 . 2	0 . 2	0 . 2	0 . 0
	1 . 0 L x	X+	6 . 4	7 . 7	8 . 7	9 . 6	10 . 4	11 . 7	12 . 5	13 . 0	13 . 1	13 . 0