

屋内照明器具特性	
品番 (品名)	NNCF42755J (J Y O U J I _ W A L L)
光源	LED5000_85_6000 ×1 6000.0 lm
管理番号	K0194240 (0) DB 1
B Z 分類	BZ10/2.3/BZ9/3.5/BZ10/4.5/BZ9

器具効率		100 % 上方光束 50 % 下方光束 50 %	反射率	天井	80 %					70 %					50 %					30 %					0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
					床	10 %					10 %					10 %					10 %					0 %
						照明率 (X0.01) ZCM																				
保守率		良 中 否	0.83	0.6	43	30	22	17	39	28	20	15	32	23	17	12	25	18	13	10	4					
			0.81	0.8	51	39	30	24	47	35	27	22	38	29	23	18	30	23	18	14	7					
			0.77	1.0	57	45	36	29	52	41	33	27	42	34	27	22	34	27	22	18	10					
			1.25	63	51	42	36	57	47	39	33	47	39	32	27	37	31	26	22	13						
下方投影面積		cm ²	1.5	67	56	48	41	61	51	44	38	50	43	36	31	40	34	29	25	15						
			2.0	73	63	55	49	66	58	51	45	55	48	43	38	44	39	35	31	19						
取付高さ	器具間隔最大限		2.5	76	68	61	55	70	63	56	51	58	52	47	43	47	42	38	35	23						
	横方向 (A) 縦方向 (B)		3.0	79	72	65	59	73	66	60	55	61	55	51	46	49	45	41	38	25						
1.5m	0m	2.12m	4.0	83	76	71	66	76	71	66	61	64	59	55	52	52	49	46	43	29						
2	0	2.7	5.0	85	80	75	70	79	74	69	65	66	62	59	55	54	51	49	46	31						
2.5	0	3.29	7.0	88	84	80	76	81	78	74	71	69	66	63	60	57	55	52	50	35						
3	0	3.9	10.0	90	87	84	81	84	81	78	75	71	69	67	64	59	57	56	54	38						

