

# 屋内照明器具特性

品番 (品名)	NTN81082 + NTN81993	
光源	LED3500_70_1215 x1      1215.0 lm	
管理番号	K0163045 (0) DR1	
BZ分類	BZ5	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %				
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
上方光束	7 %	反射率	床	10 %				10 %				10 %				10 %				0 %			
下方光束	93 %		室指数	照明率 ( X0.01 )																			
保守率	良	0.69	0.6	5.5	4.2	3.4	2.9	5.3	4.1	3.4	2.8	5.0	4.0	3.3	2.8	4.7	3.8	3.2	2.7	2.5			
	中	0.67	0.8	6.4	5.3	4.4	3.9	6.2	5.1	4.4	3.8	5.9	4.9	4.3	3.7	5.6	4.7	4.1	3.7	3.4			
	否	0.63	1.0	7.1	6.0	5.2	4.6	6.9	5.9	5.1	4.5	6.5	5.6	5.0	4.4	6.1	5.4	4.8	4.3	4.0			
			1.25	7.7	6.7	5.9	5.3	7.5	6.5	5.8	5.3	7.0	6.3	5.6	5.1	6.7	6.0	5.5	5.0	4.7			
下方投影面積	cm <sup>2</sup>		1.5	8.1	7.2	6.4	5.9	7.9	7.0	6.3	5.8	7.4	6.7	6.1	5.7	7.1	6.4	5.9	5.5	5.2			
等価発光面積	cm <sup>2</sup>		2.0	8.7	7.9	7.2	6.7	8.4	7.7	7.1	6.6	8.0	7.4	6.9	6.4	7.6	7.1	6.7	6.3	5.9			
取付高さ	器具間隔最大限		2.5	9.0	8.3	7.8	7.3	8.8	8.2	7.6	7.2	8.4	7.8	7.4	7.0	8.0	7.5	7.1	6.8	6.4			
	横方向 (A)	縦方向 (B)																					
1.5m	1.99m	2.17m	3.0	9.3	8.7	8.2	7.7	9.0	8.5	8.0	7.6	8.6	8.2	7.7	7.4	8.2	7.8	7.5	7.2	6.8			
2	2.63	2.73	4.0	9.6	9.1	8.7	8.3	9.4	8.9	8.5	8.2	8.9	8.6	8.2	7.9	8.5	8.2	8.0	7.7	7.3			
2.5	3.27	3.32	5.0	9.8	9.4	9.0	8.7	9.6	9.2	8.9	8.6	9.2	8.8	8.6	8.3	8.8	8.5	8.3	8.0	7.6			
3	3.91	3.92	7.0	10.0	9.7	9.4	9.2	9.8	9.5	9.3	9.0	9.4	9.2	8.9	8.7	9.0	8.8	8.6	8.5	8.0			
			10.0	10.2	10.0	9.8	9.6	10.0	9.8	9.6	9.4	9.6	9.4	9.3	9.1	9.2	9.1	8.9	8.8	8.3			

