

屋内照明器具特性

品番 (品名)	NTN81304 + NTN81997	
光源	LED2700_70_110 ×1	110.0 lm
管理番号	K0163037 (0) DR 1	
BZ分類	BZ6/0.7/BZ5/8.5/BZ6	

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束 13%		下方光束 87%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
室指数	照明率 (X0.01)																				ZCM
保守率	良	0.69	0.6	53	41	33	27	51	40	32	27	48	38	31	26	44	36	30	25	22	
	中	0.67	0.8	63	51	43	37	60	49	42	36	56	47	40	35	52	44	38	34	30	
	否	0.63	1.0	69	58	50	44	66	56	49	43	62	53	46	41	57	50	44	40	36	
			0.63	1.25	75	64	57	51	72	63	55	50	67	59	53	48	63	56	51	46	42
下方投影面積	cm ²		1.5	79	69	62	56	76	67	61	55	71	64	58	53	66	60	55	51	47	
等価発光面積	cm ²		2.0	84	76	70	64	82	74	68	63	76	70	65	60	71	66	62	58	53	
取付高さ	器具間隔最大限		2.5	88	81	75	70	85	79	73	68	80	74	70	66	75	70	66	63	58	
	横方向 (A)	縦方向 (B)	3.0	91	84	79	74	88	82	77	73	82	78	73	70	77	73	70	67	61	
H _m	1.29H _m	1.24H _m	4.0	94	89	84	80	91	86	82	78	86	82	78	75	81	77	74	72	66	
			5.0	96	92	88	84	93	89	86	82	88	84	81	79	83	80	77	75	69	
			7.0	98	95	92	89	96	93	90	87	90	88	85	83	85	83	81	79	73	
			10.0	100	98	95	93	98	95	93	91	92	90	89	87	87	86	84	83	77	

