

屋内照明器具特性

品番 (品名)	NTN81380 + NTN81993	
光源	LED5000_70_2030 x1 2030.0 1 m	
管理番号	K0163042 (0) DR 1	
BZ分類	BZ5	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %				
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
上方光束	12 %	反射率	床	10 %				10 %				10 %				10 %				0 %			
下方光束	88 %		室指数	照明率 (X0.01)																			
保守率	良 中 否	0.69	0.6	53	41	33	28	51	40	32	27	48	38	31	26	45	36	30	26	23			
		0.67	0.8	63	51	43	37	61	50	42	36	56	47	40	35	53	45	39	34	31			
			1.0	69	58	50	44	67	56	49	43	62	53	47	42	58	51	45	40	37			
		0.63	1.25	75	65	57	51	72	63	56	50	68	60	53	48	63	56	51	47	43			
下方投影面積	c m ²	1.5	79	70	62	56	76	68	61	55	71	64	58	53	67	61	56	51	47				
		2.0	85	77	70	64	82	75	68	63	77	71	65	61	72	67	62	59	54				
取付高さ	器具間隔最大限		2.5	88	81	75	70	86	79	74	69	80	75	70	66	75	71	67	64	59			
	横方向 (A)	縦方向 (B)	3.0	91	85	79	74	88	82	77	73	83	78	74	70	78	74	70	67	62			
1.5m	2.01 m	2.13 m	4.0	94	89	84	80	91	87	83	79	86	82	79	76	81	78	75	72	67			
2	2.64	2.68	5.0	96	92	88	84	93	89	86	83	88	85	82	79	83	81	78	76	70			
2.5	3.29	3.25	7.0	99	95	92	89	96	93	90	87	91	88	86	84	86	84	82	80	74			
3	3.92	3.83	10.0	100	98	96	93	98	96	93	91	93	91	89	87	88	86	85	84	78			

