

屋内照明器具特性	
品番 (品名)	NTN81343 + NTN81993
光源	LED3000_70_1760 ×1 1760.0 lm
管理番号	K0163042 (0) DR 1
BZ分類	BZ5

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																ZCM
保守率		良 中 否	0.69	0.6	53	41	33	28	51	40	32	27	48	38	31	26	45	36	30	26	23
			0.67	0.8	63	51	43	37	61	50	42	36	56	47	40	35	53	45	39	34	31
			0.63	1.0	69	58	50	44	67	56	49	43	62	53	47	42	58	51	45	40	37
				1.25	75	65	57	51	72	63	56	50	68	60	53	48	63	56	51	47	43
下方投影面積 等価発光面積		cm ²		1.5	79	70	62	56	76	68	61	55	71	64	58	53	67	61	56	51	47
				2.0	85	77	70	64	82	75	68	63	77	71	65	61	72	67	62	59	54
取付 高さ	器具間隔最大限		2.5	88	81	75	70	86	79	74	69	80	75	70	66	75	71	67	64	59	
	横方向 (A) 縦方向 (B)			3.0	91	85	79	74	88	82	77	73	83	78	74	70	78	74	70	67	62
1.5m	2m	2.08m	4.0	94	89	84	80	91	87	83	79	86	82	79	76	81	78	75	72	67	
2	2.64	2.64	5.0	96	92	88	84	93	89	86	83	88	85	82	79	83	81	78	76	70	
2.5	3.28	3.21	7.0	99	95	92	89	96	93	90	87	91	88	86	84	86	84	82	80	74	
3	3.92	3.81	10.0	100	98	96	93	98	96	93	91	93	91	89	87	88	86	85	84	78	

