

屋内照明器具特性

品番 (品名)	NTN82073 + NTS90551		
光源	LED3000_70_3000 ×1	3000.0 lm	
管理番号	K0153569 (4) DB1		
BZ分類	BZ1		

器具効率	100%	天井	80%				70%				50%				30%				0%																																						
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10																																							
上方光束	0%	反射率	照明率 (X0.01)																				ZCM																																		
下方光束	100%	室指数																																																							
保守率	良 0.63	0.6	0.6	76	68	63	60	75	68	63	60	74	67	63	60	72	66	62	59	58	0.8	84	77	72	69	83	77	72	69	81	76	72	69	80	75	71	68	67	1.0	89	83	78	75	88	82	78	75	86	81	77	74	84	80	77	74	73	
	中	0.6	1.25	93	88	83	80	92	87	83	80	90	86	82	80	88	84	81	79	77	1.5	96	91	87	84	94	90	87	84	92	89	86	83	90	87	85	83	81	2.0	99	95	92	89	98	94	91	89	96	93	90	88	94	91	89	87	85	
	否 0.56	2.5	101	98	95	93	100	97	94	92	97	95	93	91	95	93	92	90	88	3.0	102	99	97	95	101	98	96	94	99	97	95	93	97	95	93	92	90	4.0	104	102	100	98	103	101	99	97	100	99	97	96	98	97	96	95	92		
下方投影面積	cm ²	等価発光面積	cm ²	5.0	105	103	101	100	104	102	100	99	101	100	99	98	99	98	97	96	94	7.0	106	104	103	102	105	103	102	101	102	101	100	100	100	99	99	98	95	10.0	107	106	105	104	105	105	104	103	103	102	102	101	101	100	100	99	97
				取付	器具間隔最大限																																																				
高さ	Hm	横方向 (A)	縦方向 (B)																																																						
		0.49Hm	0.95Hm																																																						

