

# 屋内照明器具特性

|         |                     |          |
|---------|---------------------|----------|
| 品番 (品名) | NTN82104 + NTS90150 |          |
| 光源      | LED2700_70_220 ×1   | 220.0 lm |
| 管理番号    | K0156452 (2) DB1    |          |
| BZ分類    | BZ1                 |          |

|                  |                 |         |      |     |     |     |     |     |     |     |     |     |     |     |     |     |    |    |    |     |
|------------------|-----------------|---------|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|----|-----|
| 器具効率             | 100%            | 天井      | 80%  |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |    |    | 0% |     |
|                  | 上方光束<br>1%      |         | 反射率  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50 | 30 | 10 | 0%  |
| 下方光束<br>99%      |                 | 床       |      | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |    |    |    | 0%  |
| 室指数              | 照明率 ( X0.01 )   |         |      |     |     |     |     |     |     |     |     |     |     |     |     |     |    |    |    | ZCM |
| 保守率              | 良 0.63          | 0.6     | 0.6  | 72  | 63  | 57  | 53  | 70  | 62  | 57  | 53  | 69  | 61  | 56  | 53  | 67  | 60 | 56 | 53 | 51  |
|                  | 中 0.6           |         | 0.8  | 80  | 73  | 67  | 63  | 79  | 72  | 67  | 63  | 77  | 71  | 66  | 63  | 75  | 70 | 66 | 63 | 61  |
|                  | 否 0.56          |         | 1.0  | 86  | 79  | 74  | 70  | 85  | 78  | 73  | 70  | 82  | 77  | 73  | 69  | 80  | 76 | 72 | 69 | 67  |
| 下方投影面積<br>等価発光面積 | cm <sup>2</sup> | 1.25    | 90   | 84  | 80  | 76  | 89  | 83  | 79  | 76  | 87  | 82  | 78  | 75  | 85  | 81  | 77 | 75 | 73 |     |
|                  |                 | 1.5     | 93   | 88  | 84  | 81  | 92  | 87  | 83  | 80  | 90  | 86  | 82  | 79  | 88  | 84  | 81 | 79 | 77 |     |
| 取付高さ<br>Hm       | 器具間隔最大限         |         | 2.0  | 97  | 93  | 89  | 86  | 96  | 92  | 89  | 86  | 93  | 90  | 87  | 85  | 91  | 88 | 86 | 84 | 82  |
|                  | 横方向 (A)         | 縦方向 (B) | 2.5  | 99  | 96  | 93  | 90  | 98  | 95  | 92  | 90  | 96  | 93  | 90  | 88  | 93  | 91 | 89 | 87 | 85  |
|                  | 0.65Hm          | 0.85Hm  | 3.0  | 101 | 98  | 95  | 93  | 100 | 97  | 94  | 92  | 97  | 95  | 93  | 91  | 95  | 93 | 91 | 90 | 87  |
|                  |                 |         | 4.0  | 103 | 100 | 98  | 96  | 101 | 99  | 97  | 95  | 99  | 97  | 95  | 94  | 97  | 95 | 94 | 92 | 90  |
|                  |                 |         | 5.0  | 104 | 102 | 100 | 98  | 102 | 101 | 99  | 97  | 100 | 98  | 97  | 96  | 98  | 96 | 95 | 94 | 92  |
|                  |                 |         | 7.0  | 105 | 104 | 102 | 101 | 104 | 102 | 101 | 100 | 101 | 100 | 99  | 98  | 99  | 98 | 97 | 96 | 93  |
|                  |                 |         | 10.0 | 106 | 105 | 104 | 103 | 105 | 104 | 103 | 102 | 102 | 101 | 101 | 100 | 100 | 99 | 98 | 98 | 95  |

