

屋内照明器具特性

品番 (品名)	NTN82114K+NTS90101		
光源	LED2700_70_150 ×1	150.0 lm	
管理番号	K0179751(0)DR1		
BZ分類	BZ1		

器具効率	100%	天井	80%				70%				50%				30%				0%				
	上方光束		0%	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
下方光束	100%	床	10%				10%				10%				10%				0%				
室指数	照明率 (X0.01)																			ZCM			
保守率	良	0.63	0.6	0.56	0.6	78	71	66	63	77	70	66	63	76	69	65	62	74	69	65	62	61	
	中	0.6	0.6	0.56	0.8	85	79	74	71	84	78	74	71	83	77	74	71	81	76	73	70	69	
	否	0.56	1.0	0.56	1.0	90	84	80	77	89	83	79	76	87	82	79	76	85	81	78	76	74	
下方投影面積	等価発光面積	cm ²	cm ²	1.25	94	89	85	82	93	88	84	81	91	87	83	81	89	85	83	80	79		
				1.5	96	92	88	85	95	91	88	85	93	89	87	84	91	88	86	84	82		
取付高さ	器具間隔最大限		Hm	0.45Hm	0.61Hm	2.5	101	98	95	93	100	97	95	93	98	95	93	92	96	94	92	91	89
	横方向 (A)	縦方向 (B)				3.0	102	100	97	95	101	99	97	95	99	97	95	94	97	95	94	92	90
Hm	0.45Hm	0.61Hm	Hm	0.45Hm	0.61Hm	4.0	104	102	100	98	103	101	99	98	101	99	97	96	98	97	96	95	93
						5.0	105	103	101	100	104	102	101	99	101	100	99	98	99	98	99	98	97
Hm	0.45Hm	0.61Hm	Hm	0.45Hm	0.61Hm	7.0	106	105	103	102	105	103	102	101	102	101	101	100	100	99	99	98	95
						10.0	107	106	105	104	105	105	104	103	103	102	102	101	101	100	100	99	99

