

屋内照明器具特性

品番 (品名)	NTN81363 + NTN81993	
光源	LED3000_70_1525 x1 1525.0 lm	
管理番号	K0163041 (0) DR1	
BZ分類	BZ5	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %				
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
上方光束	12 %	反射率	床	10 %				10 %				10 %				10 %				0 %			
下方光束	88 %		室指数	照明率 (X0.01)																			
保守率	良 中 否	0.69	0.6	53	41	33	28	52	40	32	27	48	38	31	26	45	36	30	26	23			
		0.67	0.8	63	51	43	37	61	50	42	37	57	47	40	35	53	45	39	34	31			
			1.0	69	58	50	44	67	57	49	43	62	54	47	42	58	51	45	41	37			
		0.63	1.25	75	65	57	51	73	63	56	50	68	60	54	49	63	57	51	47	43			
下方投影面積	c m ²	1.5	79	70	62	56	77	68	61	55	72	64	58	54	67	61	56	52	47				
		2.0	85	77	70	65	82	75	69	63	77	71	66	61	72	67	63	59	54				
取付高さ	器具間隔最大限		2.5	88	81	75	70	86	79	74	69	80	75	70	66	76	71	67	64	59			
	横方向 (A)	縦方向 (B)	3.0	91	85	79	75	88	82	77	73	83	78	74	70	78	74	71	68	62			
1.5m	1.99 m	2.02 m	4.0	94	89	85	81	91	87	83	79	86	82	79	76	81	78	75	73	67			
2	2.63	2.59	5.0	96	92	88	84	94	90	86	83	88	85	82	79	83	81	78	76	70			
2.5	3.27	3.17	7.0	99	95	92	89	96	93	90	88	91	88	86	84	86	84	82	80	74			
3	3.92	3.77	10.0	101	98	96	94	98	96	94	92	93	91	89	88	88	87	85	84	78			

