

# 屋内照明器具特性

品番 (品名)	NTN82073K+NTS90354	
光源	LED3000_70_2100 ×1	2100.0 lm
管理番号	K0179711(0)DR1	
BZ分類	BZ1	

器具効率	100%	天井	80%				70%				50%				30%				0%				
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10					
上方光束	0%	壁	照明率 ( X0.01 )																				ZCM
下方光束	100%	床																					
		室指数																					
保守率	良 0.63	0.6	0.6	75	67	62	58	74	66	61	58	72	66	61	58	71	65	61	58	56			
	中 0.6	0.6	0.8	83	76	71	68	82	75	71	67	80	74	70	67	79	73	70	67	65			
	否 0.56	0.6	1.0	88	82	77	74	87	81	77	74	85	80	76	73	83	79	76	73	71			
下方投影面積	cm <sup>2</sup>	等価発光面積	cm <sup>2</sup>	1.25	92	87	83	79	91	86	82	79	89	85	81	79	87	83	80	78	76		
				1.5	95	90	86	83	94	89	86	83	92	88	85	82	90	87	84	82	80		
取付高さ	器具間隔最大限		Hm	0.57Hm	0.87Hm	2.5	101	97	94	92	99	96	94	92	97	95	92	91	95	93	91	90	88
	横方向 (A)	縦方向 (B)				3.0	102	99	97	94	101	98	96	94	99	96	94	93	96	95	93	92	89
Hm	0.57Hm	0.87Hm	4.0	104	101	99	98	102	100	99	97	100	98	97	96	98	97	95	94	92			
			5.0	105	103	101	100	103	102	100	99	101	100	99	97	99	98	97	96	94			
			7.0	106	104	103	102	105	103	102	101	102	101	100	99	100	99	99	98	95			
			10.0	106	106	105	104	105	104	104	103	103	102	102	101	101	100	100	99	97			

