

屋内照明器具特性	
品番 (品名)	NNN17911 + NNN89991
光源	LED4000_80_9225 ×1 9225.0 lm
管理番号	K0150633 (0) DB 1
BZ分類	BZ1 / 1.4 / BZ2 / 3.5 / BZ3 / 8.5 / BZ4

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		1 9 %	室指数	照明率 (X 0 . 0 1)																			Z C M
下方光束		8 1 %																					
保守率		良 中 否	0 . 7 6	0 . 6	7 1	6 3	5 8	5 4	6 9	6 2	5 7	5 4	6 6	6 0	5 6	5 3	6 2	5 7	5 4	5 1	4 9		
			0 . 7 2	0 . 8	7 7	7 0	6 4	6 1	7 5	6 8	6 3	6 0	7 1	6 5	6 1	5 8	6 7	6 3	5 9	5 7	5 3		
			0 . 6 4	1 . 0	8 1	7 4	6 9	6 5	7 9	7 2	6 8	6 4	7 4	6 9	6 5	6 2	7 0	6 6	6 3	6 0	5 6		
				1 . 2 5	8 5	7 8	7 3	7 0	8 2	7 6	7 2	6 8	7 7	7 3	6 9	6 6	7 3	6 9	6 6	6 4	5 9		
下方投影面積		c m ²	1 . 5	8 7	8 1	7 7	7 3	8 5	7 9	7 5	7 2	8 0	7 5	7 2	6 9	7 5	7 1	6 8	6 6	6 1			
等価発光面積			c m ²	2 . 0	9 1	8 6	8 2	7 8	8 8	8 3	8 0	7 6	8 3	7 9	7 6	7 3	7 7	7 4	7 2	7 0	6 4		
取付高さ	器具間隔最大限		2 . 5	9 3	8 9	8 5	8 2	9 0	8 6	8 3	8 0	8 4	8 1	7 8	7 6	7 9	7 7	7 4	7 2	6 7			
	横方向 (A)		縦方向 (B)	3 . 0	9 5	9 1	8 7	8 4	9 2	8 8	8 5	8 2	8 6	8 3	8 0	7 8	8 0	7 8	7 6	7 4	6 8		
H m	0 . 9 9 H m	1 . 0 0 H m	4 . 0	9 7	9 3	9 1	8 8	9 4	9 1	8 8	8 6	8 8	8 5	8 3	8 1	8 2	8 0	7 9	7 7	7 0			
			5 . 0	9 8	9 5	9 3	9 0	9 5	9 2	9 0	8 8	8 9	8 7	8 5	8 3	8 3	8 2	8 0	7 9	7 2			
			7 . 0	1 0 0	9 7	9 5	9 3	9 6	9 4	9 3	9 1	9 0	8 9	8 7	8 6	8 5	8 3	8 2	8 1	7 4			
			1 0 . 0	1 0 1	9 9	9 8	9 6	9 8	9 6	9 5	9 3	9 1	9 0	8 9	8 8	8 6	8 5	8 4	8 3	7 5			

