

屋内照明器具特性	
品番 (品名)	NSEK47622J+NNL4600HNT
光源	LED5000_85_6780 ×1 6780.0 lm
管理番号	K0145987 (0) DB1
BZ分類	BZ5/1.4/BZ4

器具効率			100 %		反射率	天井	80 %				70 %				50 %				30 %				0 %
						壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
						床	10 %				10 %				10 %				10 %				0 %
						室指数	照明率 (X0.01)																
保守率			良 中 否	0.81	0.6	57	45	37	31	56	44	37	31	53	43	36	31	51	42	36	31	29	
				0.77	0.8	67	56	48	42	66	55	47	42	63	53	47	42	60	52	46	41	39	
				0.68	1.0	74	63	56	50	72	62	55	50	69	61	54	49	67	59	54	49	47	
					1.25	80	70	63	58	78	69	63	57	75	68	62	57	73	66	61	56	54	
下方投影面積			cm ²	1.5	84	76	69	63	83	75	68	63	79	73	67	63	77	71	66	62	60		
				等価発光面積	cm ²	2.0	90	83	77	72	88	82	76	72	85	80	75	71	82	78	74	70	68
取付高さ		器具間隔最大限			2.5	93	87	82	78	92	86	82	77	89	84	80	77	86	82	79	76	73	
		横方向 (A)		縦方向 (B)		3.0	96	91	86	82	94	90	85	82	91	87	84	81	89	85	82	80	77
1.5m		2.01 m		2.15 m		4.0	99	95	91	88	98	94	90	87	95	92	89	86	92	89	87	85	82
2		2.66		2.71		5.0	101	97	94	92	99	96	93	91	97	94	92	89	94	92	90	88	85
2.5		3.3		3.29		7.0	103	100	98	96	102	99	97	95	99	97	95	94	97	95	93	92	89
3		3.94		3.88		10.0	105	103	101	99	103	102	100	99	101	99	98	97	98	97	96	95	92

