

屋内照明器具特性	
品番 (品名)	NSEK47632J+NEL4300EX
光源	LED5000_85_3150 ×1 3150.0 lm
管理番号	K0193797 (0) DB 1
BZ分類	BZ4

器具効率		100 %		反射率	天井	80 %				70 %				50 %				30 %				0 %
					壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
					床	10 %				10 %				10 %				10 %				0 %
					室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.81	0.6	60	49	41	36	59	48	41	36	57	47	41	36	55	46	40	36	34	
			0.77	0.8	70	60	52	47	69	59	52	47	66	58	52	47	64	57	51	47	45	
			0.68	1.0	77	67	60	55	75	66	60	55	73	65	59	54	70	63	58	54	52	
				1.25	83	74	67	62	81	73	67	62	78	71	66	62	76	70	65	61	59	
下方投影面積		cm ²		1.5	87	79	73	68	85	78	72	67	82	76	71	67	80	74	70	66	64	
			等価発光面積	cm ²	2.0	92	85	80	76	90	84	79	75	87	82	78	74	85	80	77	74	71
取付 高さ	器具間隔最大限			2.5	95	90	85	81	94	88	84	80	91	86	83	79	88	85	81	79	76	
	横方向 (A)		縦方向 (B)	3.0	97	92	88	85	96	91	88	84	93	89	86	83	90	87	85	82	80	
1.5m	1.92 m	2.07 m	4.0	100	96	93	90	99	95	92	89	96	93	90	88	93	91	89	87	84		
2	2.52	2.61	5.0	102	99	96	93	100	97	95	93	98	95	93	91	95	93	91	90	87		
2.5	3.14	3.17	7.0	104	101	99	97	102	100	98	96	100	98	96	95	97	96	95	93	90		
3	3.75	3.75	10.0	105	103	102	100	104	102	101	99	101	100	99	98	99	98	97	96	93		

