

屋内照明器具特性

品番 (品名)	NTS51314 + NTS91052B + NTS90	
光源	LED2700_70_760 x1	760.0 lm
管理番号	K0156322 (1) DJ 1	
BZ分類	BZ1	

器具効率	103%	天井	80%				70%				50%				30%				0%	
	上方光束 0%		下方光束 103%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10
室指数	照明率 (X0.01)																			ZCM
保守率	良	0.67	0.6	1.02	0.99	0.98	0.96	1.01	0.99	0.97	0.96	1.01	0.99	0.97	0.96	1.00	0.98	0.97	0.96	0.96
	中	0.63	0.8	1.04	1.01	1.00	0.99	1.03	1.01	1.00	0.98	1.02	1.00	0.99	0.98	1.01	1.00	0.99	0.98	0.97
	否	0.56	1.0	1.05	1.03	1.01	1.00	1.04	1.02	1.01	1.00	1.03	1.02	1.00	0.99	1.02	1.01	1.00	0.99	0.98
下方投影面積	等価発光面積	cm ²	1.25	1.06	1.04	1.03	1.01	1.05	1.04	1.02	1.01	1.04	1.03	1.01	1.01	1.03	1.02	1.01	1.00	0.99
			1.5	1.07	1.05	1.04	1.02	1.06	1.04	1.03	1.02	1.05	1.03	1.02	1.01	1.03	1.02	1.01	1.01	1.01
取付高さ	器具間隔最大限		2.5	1.08	1.07	1.06	1.05	1.07	1.06	1.05	1.04	1.06	1.05	1.04	1.03	1.04	1.03	1.03	1.02	1.00
	横方向 (A)	縦方向 (B)	3.0	1.09	1.08	1.07	1.06	1.08	1.07	1.06	1.05	1.06	1.05	1.05	1.04	1.04	1.04	1.03	1.03	1.01
Hm	0.23Hm	0.23Hm	4.0	1.09	1.08	1.08	1.07	1.08	1.07	1.07	1.06	1.06	1.06	1.05	1.05	1.05	1.04	1.04	1.03	1.01
			5.0	1.10	1.09	1.08	1.08	1.09	1.08	1.07	1.07	1.07	1.06	1.06	1.05	1.05	1.04	1.04	1.04	1.01
			7.0	1.10	1.09	1.09	1.08	1.09	1.08	1.08	1.07	1.07	1.06	1.06	1.06	1.05	1.05	1.04	1.04	1.02
			10.0	1.10	1.10	1.10	1.09	1.09	1.09	1.08	1.08	1.07	1.07	1.07	1.06	1.05	1.05	1.05	1.04	1.02

