

屋内照明器具特性

品番 (品名)	NTS51321+NTS91052B+NTS90	
光源	LED4000_70_440 x1	440.0 lm
管理番号	K0156165(3)DJ1	
BZ分類	BZ1	

器具効率	102%	天井	80%				70%				50%				30%				0%	
	上方光束 0%		下方光束 102%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10
室指数	照明率 (X0.01)																			ZCM
保守率	良	0.67	0.6	1.00	0.97	0.95	0.94	0.99	0.97	0.95	0.94	0.98	0.96	0.95	0.93	0.98	0.96	0.94	0.93	0.93
	中	0.63	0.8	1.02	0.99	0.98	0.96	1.01	0.99	0.97	0.96	1.00	0.98	0.97	0.96	1.00	0.98	0.97	0.96	0.95
	否	0.56	1.0	1.03	1.01	0.99	0.98	1.03	1.01	0.99	0.98	1.02	1.00	0.98	0.97	1.01	0.99	0.98	0.97	0.96
下方投影面積 等価発光面積	cm ²		1.25	1.05	1.02	1.01	1.00	1.04	1.02	1.00	0.99	1.03	1.01	1.00	0.99	1.01	1.00	0.99	0.98	0.97
	cm ²		1.5	1.05	1.03	1.02	1.01	1.05	1.03	1.02	1.00	1.03	1.02	1.01	1.00	1.02	1.01	1.00	0.99	0.98
取付高さ	器具間隔最大限		2.5	1.07	1.06	1.05	1.04	1.06	1.05	1.04	1.03	1.05	1.04	1.03	1.02	1.03	1.02	1.01	1.01	0.99
	Hm	0.31Hm	3.0	1.08	1.06	1.05	1.04	1.07	1.06	1.05	1.04	1.05	1.04	1.03	1.03	1.03	1.03	1.02	1.01	1.00
Hm	0.31Hm	0.31Hm	4.0	1.08	1.07	1.06	1.06	1.07	1.06	1.06	1.05	1.05	1.05	1.04	1.03	1.04	1.03	1.03	1.02	1.00
			5.0	1.09	1.08	1.07	1.06	1.08	1.07	1.06	1.06	1.06	1.05	1.05	1.04	1.04	1.03	1.03	1.02	1.00
			7.0	1.09	1.08	1.08	1.07	1.08	1.07	1.07	1.06	1.06	1.06	1.05	1.05	1.04	1.04	1.03	1.03	1.01
			10.0	1.09	1.09	1.09	1.08	1.08	1.08	1.07	1.07	1.06	1.06	1.06	1.05	1.04	1.04	1.04	1.03	1.01

