

# 屋内照明器具特性

|         |                    |          |
|---------|--------------------|----------|
| 品番 (品名) | NTS72220W+NTS90101 |          |
| 光源      | LED5000_85_975 ×1  | 975.0 1m |
| 管理番号    | K0166619(1)DJ1     |          |
| BZ分類    | BZ1                |          |

|        |                 |         |      |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |     |
|--------|-----------------|---------|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|-----|
| 器具効率   | 101%            | 天井      | 80%  |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0% |     |
|        | 上方光束<br>0%      |         | 壁    | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10 | 0%  |
| 下方光束   | 101%            | 床       |      | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |    | 0%  |
| 室指数    | 照明率 ( X0.01 )   |         |      |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    | ZCM |
| 保守率    | 良 0.81          | 0.6     | 85   | 79  | 76  | 73  | 85  | 79  | 75  | 73  | 83  | 78  | 75  | 73  | 82  | 78  | 75  | 73  | 71 |     |
|        | 中 0.77          |         | 0.8  | 91  | 86  | 82  | 80  | 90  | 86  | 82  | 80  | 89  | 85  | 82  | 79  | 88  | 84  | 81  | 79 | 78  |
|        | 否 0.68          |         | 1.0  | 95  | 90  | 87  | 84  | 94  | 90  | 87  | 84  | 92  | 89  | 86  | 84  | 91  | 88  | 85  | 83 | 82  |
| 下方投影面積 | cm <sup>2</sup> | 1.25    | 98   | 94  | 91  | 88  | 97  | 93  | 90  | 88  | 95  | 92  | 89  | 87  | 94  | 91  | 89  | 87  | 86 |     |
|        |                 | 1.5     | 100  | 96  | 93  | 91  | 99  | 95  | 93  | 91  | 97  | 94  | 92  | 90  | 95  | 93  | 91  | 89  | 88 |     |
| 等価発光面積 | cm <sup>2</sup> | 2.0     | 102  | 99  | 97  | 95  | 101 | 98  | 96  | 94  | 99  | 97  | 95  | 94  | 97  | 96  | 94  | 93  | 91 |     |
|        |                 | 2.5     | 104  | 101 | 99  | 97  | 103 | 100 | 98  | 97  | 101 | 99  | 97  | 96  | 99  | 97  | 96  | 95  | 93 |     |
| 取付高さ   | 器具間隔最大限         |         | 3.0  | 105 | 102 | 101 | 99  | 104 | 102 | 100 | 98  | 101 | 100 | 98  | 97  | 100 | 98  | 97  | 94 |     |
|        | 横方向 (A)         | 縦方向 (B) | 4.0  | 106 | 104 | 103 | 101 | 105 | 103 | 102 | 101 | 103 | 101 | 100 | 99  | 101 | 100 | 99  | 96 |     |
| Hm     | 0.36Hm          | 0.36Hm  | 5.0  | 106 | 105 | 104 | 103 | 105 | 104 | 103 | 102 | 103 | 102 | 101 | 100 | 101 | 100 | 100 | 97 |     |
|        |                 |         | 7.0  | 107 | 106 | 105 | 104 | 106 | 105 | 104 | 104 | 103 | 103 | 102 | 102 | 101 | 101 | 100 | 98 |     |
|        |                 |         | 10.0 | 108 | 107 | 106 | 106 | 107 | 106 | 105 | 105 | 105 | 104 | 103 | 103 | 102 | 102 | 101 | 99 |     |

