

屋内照明器具特性

品番(品名)	NTS51318+NTS91052W+NTS90	
光源	LED3000_70_400 x1	400.0 lm
管理番号	K0156322(1)DJ1	
BZ分類	BZ1	

器具効率	103%	天井	80%				70%				50%				30%				0%	
	上方光束 0%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	103%	床	10%				10%				10%				10%				0%	
室指数	照明率 (X0.01)																			ZCM
保守率	良 0.67	0.6	1.02	0.99	0.98	0.96	1.01	0.99	0.97	0.96	1.01	0.99	0.97	0.96	1.00	0.98	0.97	0.96	0.96	
	中 0.63	0.8	1.04	1.01	1.00	0.99	1.03	1.01	1.00	0.98	1.02	1.00	0.99	0.98	1.01	1.00	0.99	0.98	0.97	
	否 0.56	1.0	1.05	1.03	1.01	1.00	1.04	1.02	1.01	1.00	1.03	1.02	1.00	0.99	1.02	1.01	1.00	0.99	0.98	
下方投影面積	cm ²	1.25	1.06	1.04	1.03	1.01	1.05	1.04	1.02	1.01	1.04	1.03	1.01	1.01	1.03	1.02	1.01	1.00	0.99	
		1.5	1.07	1.05	1.04	1.02	1.06	1.04	1.03	1.02	1.05	1.03	1.02	1.01	1.03	1.02	1.01	1.01	0.99	
等価発光面積	cm ²	2.0	1.08	1.06	1.05	1.04	1.07	1.06	1.04	1.03	1.05	1.04	1.03	1.03	1.04	1.03	1.02	1.02	1.00	
		2.5	1.08	1.07	1.06	1.05	1.07	1.06	1.05	1.04	1.06	1.05	1.04	1.03	1.04	1.03	1.03	1.02	1.00	
取付高さ	器具間隔最大限		3.0	1.09	1.08	1.07	1.06	1.08	1.07	1.06	1.05	1.06	1.05	1.05	1.04	1.04	1.03	1.03	1.01	
	Hm	0.23Hm	0.23Hm	4.0	1.09	1.08	1.08	1.07	1.08	1.07	1.07	1.06	1.06	1.05	1.05	1.04	1.04	1.03	1.01	
			5.0	1.10	1.09	1.08	1.08	1.09	1.08	1.07	1.07	1.06	1.06	1.05	1.05	1.04	1.04	1.03	1.01	
			7.0	1.10	1.09	1.09	1.08	1.09	1.08	1.08	1.07	1.07	1.06	1.06	1.05	1.05	1.04	1.04	1.02	
			10.0	1.10	1.10	1.10	1.09	1.09	1.09	1.08	1.08	1.07	1.07	1.07	1.06	1.05	1.05	1.04	1.02	

