

屋内照明器具特性

品番 (品名)	NTS51313 + NTS91052 W + NTS90	
光源	LED3000_70_495 x1	495.0 lm
管理番号	K0156322 (1) DJ 1	
BZ分類	BZ1	

器具効率	103%	天井	80%				70%				50%				30%				0%				
	上方光束 0%		下方光束 103%	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
反射率		壁	10%				10%				10%				10%				0%				
床		室指数	照明率 (X0.01)																				ZCM
保守率	良 中 否	0.67 0.63 0.56	0.6	1.02	0.99	0.98	0.96	1.01	0.99	0.97	0.96	1.01	0.99	0.97	0.96	1.00	0.98	0.97	0.96	0.96			
下方投影面積 等価発光面積	cm ² cm ²		0.8	1.04	1.01	1.00	0.99	1.03	1.01	1.00	0.98	1.02	1.00	0.99	0.98	1.01	1.00	0.99	0.98	0.97			
取付高さ	器具間隔最大限		1.0	1.05	1.03	1.01	1.00	1.04	1.02	1.01	1.00	1.03	1.02	1.00	0.99	1.02	1.01	1.00	0.99	0.98			
Hm	横方向 (A)	縦方向 (B)	1.25	1.06	1.04	1.03	1.01	1.05	1.04	1.02	1.01	1.04	1.03	1.01	1.01	1.03	1.02	1.01	1.00	0.99			
	0.23Hm	0.23Hm	1.5	1.07	1.05	1.04	1.02	1.06	1.04	1.03	1.02	1.05	1.03	1.02	1.01	1.03	1.02	1.01	1.01	0.99			
			2.0	1.08	1.06	1.05	1.04	1.07	1.06	1.04	1.03	1.05	1.04	1.03	1.03	1.04	1.03	1.02	1.02	1.00			
			2.5	1.08	1.07	1.06	1.05	1.07	1.06	1.05	1.04	1.06	1.05	1.04	1.03	1.04	1.03	1.03	1.02	1.00			
			3.0	1.09	1.08	1.07	1.06	1.08	1.07	1.06	1.05	1.06	1.05	1.05	1.04	1.04	1.04	1.03	1.03	1.01			
			4.0	1.09	1.08	1.08	1.07	1.08	1.07	1.07	1.06	1.06	1.06	1.05	1.05	1.05	1.04	1.04	1.03	1.01			
			5.0	1.10	1.09	1.08	1.08	1.09	1.08	1.07	1.07	1.07	1.06	1.06	1.05	1.05	1.04	1.04	1.04	1.01			
			7.0	1.10	1.09	1.09	1.08	1.09	1.08	1.08	1.07	1.07	1.06	1.06	1.06	1.05	1.05	1.04	1.04	1.02			
			10.0	1.10	1.10	1.10	1.09	1.09	1.09	1.08	1.08	1.07	1.07	1.07	1.06	1.05	1.05	1.05	1.04	1.02			

