

# 屋内照明器具特性

品番 (品名)	NTS66151 + NTS90151 + NTS910	
光源	LED4000_70_2805 ×1      2805.0 lm	
管理番号	K0168007 (1) DJ 1	
BZ分類	BZ1	

器具効率	100%	天井	80%				70%				50%				30%				0%	
	上方光束		0%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10
下方光束	100%	床	10%				10%				10%				10%				0%	
室指数	照明率 ( X0.01 )																			ZCM
保守率	良	0.63	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6
	中	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6
	否	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56
下方投影面積	等価発光面積	cm <sup>2</sup>		2.5	3.0	3.5	4.0	4.5	5.0	5.5	6.0	6.5	7.0	7.5	8.0	8.5	9.0	9.5	10.0	
		cm <sup>2</sup>		1.25	1.5	1.75	2.0	2.25	2.5	2.75	3.0	3.25	3.5	3.75	4.0	4.25	4.5	4.75	5.0	5.25
取付高さ	器具間隔最大限		Hm		0.67Hm	0.67Hm	0.67Hm	0.67Hm	0.67Hm	0.67Hm	0.67Hm	0.67Hm	0.67Hm	0.67Hm	0.67Hm	0.67Hm	0.67Hm	0.67Hm	0.67Hm	0.67Hm
	横方向 (A)	縦方向 (B)	0.67Hm	0.67Hm	0.67Hm	0.67Hm	0.67Hm	0.67Hm	0.67Hm	0.67Hm	0.67Hm	0.67Hm	0.67Hm	0.67Hm	0.67Hm	0.67Hm	0.67Hm	0.67Hm	0.67Hm	0.67Hm
5.0	7.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
7.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0

