

屋内照明器具特性	
品番 (品名)	NYM20112Z+NYK00108
光源	LED5000_85_18100 ×1 18100.0 1 m
管理番号	K0174956(2)D 1
BZ分類	BZ1/1.4/BZ2

器具効率	100%	天井	80%				70%				50%				30%				0%				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%				
上方光束	1%	床	10%				10%				10%				10%				0%				
下方光束	99%	室指数	照明率 (X0.01)																				ZCM
保守率	良	0.77	0.6	72	64	58	54	71	63	58	54	69	62	58	54	68	61	57	54	52			
	中	0.72	0.8	80	73	67	63	79	72	67	63	77	71	66	63	75	70	66	62	61			
	否	0.68	1.0	86	78	73	69	84	78	73	69	82	76	72	69	80	75	71	68	67			
			1.25	90	84	79	75	89	83	78	75	86	81	77	74	84	80	76	74	72			
下方投影面積	c m ²		1.5	93	87	83	79	91	86	82	79	89	84	81	78	87	83	80	77	75			
	等価発光面積		c m ²	2.0	96	92	88	85	95	91	87	84	93	89	86	83	90	87	85	82	80		
取付高さ	器具間隔最大限		2.5	99	95	91	89	97	94	91	88	95	92	89	87	92	90	88	86	83			
	横方向 (A)	縦方向 (B)	3.0	100	97	94	91	99	96	93	91	96	94	91	89	94	92	90	88	86			
H m	0.83 H m	0.83 H m	4.0	102	100	97	95	101	98	96	94	98	96	94	93	96	94	93	91	89			
			5.0	103	101	99	97	102	100	98	96	99	98	96	95	97	96	94	93	90			
			7.0	105	103	102	100	103	102	100	99	101	100	98	97	98	97	96	95	93			
			10.0	106	105	103	102	104	103	102	101	102	101	100	99	99	99	98	97	94			

