

屋内照明器具特性

品番 (品名)	NYM20113Z+NYK00101	
光源	LED5000_85_22500 ×1	22500.0 1 m
管理番号	K0174952(0)D 1	
BZ分類	BZ1/1.1/BZ2	

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束 1%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
下方光束	99%	床		10%				10%				10%				10%				0%	
室指数	照明率 (X0.01)																				ZCM
保守率	良	0.77	0.6	72	64	58	54	71	63	58	54	69	62	57	54	68	61	57	54	52	
	中	0.72	0.8	80	72	67	63	79	72	67	63	77	71	66	63	75	70	66	62	61	
	否	0.68	1.0	85	78	73	69	84	78	73	69	82	76	72	69	80	75	71	68	67	
			1.25	90	83	79	75	89	83	78	75	86	81	77	74	84	80	76	74	72	
下方投影面積	c m ²		1.5	93	87	83	79	91	86	82	79	89	85	81	78	87	83	80	77	75	
	等価発光面積		c m ²	2.0	96	92	88	85	95	91	87	84	93	89	86	83	90	87	85	83	80
取付高さ	器具間隔最大限		2.5	99	95	91	89	97	94	91	88	95	92	89	87	93	90	88	86	84	
	横方向 (A)	縦方向 (B)	3.0	100	97	94	91	99	96	93	91	97	94	92	90	94	92	90	88	86	
H m	0.83 H m	0.83 H m	4.0	102	100	97	95	101	99	96	94	99	96	95	93	96	95	93	92	89	
			5.0	103	101	99	97	102	100	98	97	100	98	96	95	97	96	95	94	91	
			7.0	105	103	102	100	104	102	101	99	101	100	99	98	99	98	97	96	93	
			10.0	106	105	104	102	105	103	102	102	102	101	100	100	100	99	98	98	95	

