

| 屋内照明器具特性 |                                |
|----------|--------------------------------|
| 品番 (品名)  | NYM20115K+NYK00109             |
| 光源       | LED5000_85_35000 ×1 35000.0 lm |
| 管理番号     | K0168491(0)DY1                 |
| BZ分類     | BZ1/0.7/BZ2                    |

|        |                            |          |                 |     |     |     |     |     |     |     |     |     |     |     |     |     |    |    |    |    |  |  |
|--------|----------------------------|----------|-----------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|----|----|--|--|
| 器具効率   | 100%                       | 天井       | 80%             |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |    |    | 0% |    |  |  |
|        |                            | 壁        | 70              | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30 | 10 | 0% |    |  |  |
| 上方光束   | 1%                         | 床        | 10%             |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |    |    | 0% |    |  |  |
| 下方光束   | 99%                        | 室指数      | 照明率 (X0.01) ZCM |     |     |     |     |     |     |     |     |     |     |     |     |     |    |    |    |    |  |  |
| 保守率    | 良 0.77<br>中 0.72<br>否 0.68 | 0.6      | 71              | 62  | 57  | 53  | 70  | 62  | 56  | 53  | 68  | 61  | 56  | 52  | 67  | 60  | 56 | 52 | 51 |    |  |  |
|        |                            | 0.8      | 80              | 72  | 66  | 62  | 79  | 71  | 66  | 62  | 76  | 70  | 65  | 62  | 75  | 69  | 65 | 62 | 60 |    |  |  |
|        |                            | 1.0      | 85              | 78  | 73  | 69  | 84  | 77  | 72  | 69  | 82  | 76  | 71  | 68  | 80  | 75  | 71 | 68 | 66 |    |  |  |
|        |                            | 1.25     | 89              | 83  | 78  | 75  | 88  | 82  | 78  | 74  | 86  | 81  | 77  | 74  | 84  | 80  | 76 | 73 | 71 |    |  |  |
| 下方投影面積 | c m <sup>2</sup>           | 1.5      | 92              | 87  | 82  | 79  | 91  | 86  | 82  | 78  | 89  | 84  | 81  | 78  | 87  | 83  | 80 | 77 | 75 |    |  |  |
|        |                            | 2.0      | 96              | 92  | 88  | 85  | 95  | 91  | 87  | 84  | 93  | 89  | 86  | 83  | 90  | 87  | 85 | 82 | 80 |    |  |  |
| 取付高さ   | 器具間隔最大限                    |          | 2.5             | 99  | 95  | 91  | 88  | 97  | 94  | 91  | 88  | 95  | 92  | 89  | 87  | 93  | 90 | 88 | 86 | 84 |  |  |
|        | 横方向 (A)                    | 縦方向 (B)  | 3.0             | 100 | 97  | 94  | 91  | 99  | 96  | 93  | 91  | 96  | 94  | 92  | 89  | 94  | 92 | 90 | 88 | 86 |  |  |
| H m    | 0.93 H m                   | 0.93 H m | 4.0             | 102 | 99  | 97  | 95  | 101 | 98  | 96  | 94  | 98  | 96  | 95  | 93  | 96  | 94 | 93 | 91 | 89 |  |  |
|        |                            |          | 5.0             | 103 | 101 | 99  | 97  | 102 | 100 | 98  | 97  | 100 | 98  | 96  | 95  | 97  | 96 | 95 | 93 | 91 |  |  |
|        |                            |          | 7.0             | 105 | 103 | 102 | 100 | 103 | 102 | 101 | 99  | 101 | 100 | 99  | 97  | 99  | 98 | 97 | 96 | 93 |  |  |
|        |                            |          | 10.0            | 106 | 104 | 103 | 102 | 104 | 103 | 102 | 101 | 102 | 101 | 100 | 99  | 100 | 99 | 98 | 98 | 95 |  |  |

