

屋内照明器具特性	
品番 (品名)	NTN83520
光源	LED5000_70_2550 ×1 2550.0 lm
管理番号	K0167967 (0) DY1
BZ分類	BZ6

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %					
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %					
				床	10 %				10 %				10 %				10 %				0 %					
上方光束		19 %	室指数	照明率 (X0.01)																			Z	C		M
下方光束		81 %																								
保守率		良 中 否	0.69	0.6	51	38	30	25	49	37	29	24	44	34	28	23	40	32	26	22	19					
			0.67	0.8	60	48	40	34	57	46	38	33	52	43	36	31	48	40	34	29	26					
			0.63	1.0	66	55	46	40	63	53	45	39	58	49	42	37	53	45	40	35	31					
				1.25	72	61	53	47	69	59	52	46	63	55	48	43	57	51	45	41	36					
下方投影面積		cm ²	1.5	76	66	58	52	73	64	57	51	67	59	53	48	61	55	50	45	40						
等価発光面積		cm ²	2.0	82	73	66	60	78	71	64	59	72	65	60	55	66	61	56	52	46						
取付 高さ	器具間隔最大限		2.5	85	78	72	66	82	75	69	64	75	70	65	61	69	65	61	57	51						
	横方向 (A)	縦方向 (B)	3.0	88	81	76	71	85	78	73	68	78	73	68	65	72	68	64	61	54						
1.5m	2.08 m	2.01 m	4.0	91	86	81	77	88	83	78	74	81	77	73	70	75	72	69	66	59						
2	2.75	2.59	5.0	94	89	85	81	90	86	82	78	84	80	77	74	77	74	72	69	62						
2.5	3.43	3.2	7.0	96	93	89	86	93	89	86	83	86	83	81	78	80	78	76	74	66						
3	4.11	3.81	10.0	98	96	93	90	95	92	90	88	88	86	84	82	82	80	79	77	69						

