

# 屋内照明器具特性

|         |                          |          |
|---------|--------------------------|----------|
| 品番 (品名) | NTS51327+NTS91052B+NTS90 |          |
| 光源      | LED3500_70_345 x1        | 345.0 lm |
| 管理番号    | K0156165(3)DJ1           |          |
| BZ分類    | BZ1                      |          |

|                  |                 |        |              |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |
|------------------|-----------------|--------|--------------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| 器具効率             | 102%            | 天井     | 80%          |      |      |      | 70%  |      |      |      | 50%  |      |      |      | 30%  |      |      |      | 0%   |      |
|                  | 上方光束<br>0%      |        | 下方光束<br>102% | 反射率  | 70   | 50   | 30   | 10   | 70   | 50   | 30   | 10   | 70   | 50   | 30   | 10   | 70   | 50   | 30   | 10   |
| 室指数              | 照明率 ( X0.01 )   |        |              |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      | ZCM  |
| 保守率              | 良               | 0.67   | 0.6          | 1.00 | 0.97 | 0.95 | 0.94 | 0.99 | 0.97 | 0.95 | 0.94 | 0.98 | 0.96 | 0.95 | 0.93 | 0.98 | 0.96 | 0.94 | 0.93 | 0.93 |
|                  | 中               | 0.63   | 0.8          | 1.02 | 0.99 | 0.98 | 0.96 | 1.01 | 0.99 | 0.97 | 0.96 | 1.00 | 0.98 | 0.97 | 0.96 | 1.00 | 0.98 | 0.97 | 0.96 | 0.95 |
|                  | 否               | 0.56   | 1.0          | 1.03 | 1.01 | 0.99 | 0.98 | 1.03 | 1.01 | 0.99 | 0.98 | 1.02 | 1.00 | 0.98 | 0.97 | 1.01 | 0.99 | 0.98 | 0.97 | 0.96 |
| 下方投影面積<br>等価発光面積 | cm <sup>2</sup> |        | 1.25         | 1.05 | 1.02 | 1.01 | 1.00 | 1.04 | 1.02 | 1.00 | 0.99 | 1.03 | 1.01 | 1.00 | 0.99 | 1.01 | 1.00 | 0.99 | 0.98 | 0.97 |
|                  | cm <sup>2</sup> |        | 1.5          | 1.05 | 1.03 | 1.02 | 1.01 | 1.05 | 1.03 | 1.02 | 1.00 | 1.03 | 1.02 | 1.01 | 1.00 | 1.02 | 1.01 | 1.00 | 0.99 | 0.98 |
| 取付高さ             | 器具間隔最大限         |        | 2.5          | 1.07 | 1.06 | 1.05 | 1.04 | 1.06 | 1.05 | 1.04 | 1.03 | 1.05 | 1.04 | 1.03 | 1.02 | 1.03 | 1.02 | 1.01 | 1.00 | 0.99 |
|                  | Hm              | 0.31Hm | 3.0          | 1.08 | 1.06 | 1.05 | 1.04 | 1.07 | 1.06 | 1.05 | 1.04 | 1.05 | 1.04 | 1.03 | 1.03 | 1.03 | 1.03 | 1.02 | 1.01 | 1.00 |
| Hm               | 0.31Hm          | 0.31Hm | 4.0          | 1.08 | 1.07 | 1.06 | 1.06 | 1.07 | 1.06 | 1.06 | 1.05 | 1.05 | 1.05 | 1.04 | 1.03 | 1.04 | 1.03 | 1.03 | 1.02 | 1.00 |
|                  |                 |        | 5.0          | 1.09 | 1.08 | 1.07 | 1.06 | 1.08 | 1.07 | 1.06 | 1.06 | 1.06 | 1.05 | 1.05 | 1.04 | 1.04 | 1.03 | 1.03 | 1.02 | 1.00 |
|                  |                 |        | 7.0          | 1.09 | 1.08 | 1.08 | 1.07 | 1.08 | 1.07 | 1.07 | 1.06 | 1.06 | 1.06 | 1.05 | 1.05 | 1.04 | 1.04 | 1.03 | 1.03 | 1.01 |
|                  |                 |        | 10.0         | 1.09 | 1.09 | 1.09 | 1.08 | 1.08 | 1.08 | 1.07 | 1.07 | 1.06 | 1.06 | 1.06 | 1.05 | 1.04 | 1.04 | 1.04 | 1.03 | 1.01 |

