

屋内照明器具特性

品番 (品名)	NTS51328 + NTS91052B + NTS90	
光源	LED3000_70_670 x1	670.0 lm
管理番号	K0156165 (3) DJ 1	
BZ分類	BZ1	

器具効率	102%	天井	80%				70%				50%				30%				0%										
	上方光束 0%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%									
下方光束	102%	床		10%				10%				10%				10%				0%									
保守率	良 中 否	0.67 0.63 0.56	室指数	照明率 (X0.01)																ZCM									
下方投影面積 等価発光面積	cm ² cm ²		0.6	1.0	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	100	97	95	94	99	97	95	94	98	96	95	93	98	96	94	93	93
取付高さ	器具間隔最大限		0.8	1.2	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	102	99	98	96	101	99	97	96	100	98	97	96	100	98	97	96	95
	Hm	0.31Hm	1.0	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	103	101	99	98	103	101	99	98	102	100	98	97	101	99	98	97	96	
	横方向 (A)	縦方向 (B)	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	105	102	101	100	104	102	100	99	103	101	100	99	101	100	99	98	97	
			1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	105	103	102	101	105	103	102	100	103	102	101	100	102	101	100	99	98		
			2.0	2.5	3.0	4.0	5.0	7.0	10.0	107	105	104	102	106	104	103	102	104	103	102	101	103	102	101	100	99			
			2.5	3.0	4.0	5.0	7.0	10.0	107	106	105	104	106	105	104	103	105	104	103	102	103	102	101	100	99				
			3.0	4.0	5.0	7.0	10.0	108	106	105	104	107	106	105	104	105	104	103	103	103	103	103	102	101	100				
			4.0	5.0	7.0	10.0	108	107	106	105	107	106	105	104	105	104	103	104	103	103	103	103	102	101	100				
			5.0	7.0	10.0	109	108	107	106	108	107	106	105	104	105	104	103	104	103	103	103	103	102	101	100				
			7.0	10.0	109	108	107	106	108	107	106	105	104	105	104	103	104	103	103	103	103	102	101	100					
			10.0	109	108	107	106	108	107	106	105	104	105	104	103	104	103	103	103	103	103	102	101	100					

