

屋内照明器具特性	
品番 (品名)	NTN88006B
光源	LLD3020CU1 ×1 615.0 lm
管理番号	K0181913 (0) DR1
BZ分類	BZ1

器具効率		83 %	反 射 率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束		0 %	室指数	床	10 %				10 %				10 %				10 %				0 %
下方光束		83 %		照明率 (X0.01) ZCM																	
保守率		良	0.6	71	66	63	61	70	66	63	61	69	65	62	61	68	65	62	60	60	
		中	0.8	75	71	68	66	74	71	68	66	73	70	67	65	72	69	67	65	64	
		否	1.0	78	74	71	69	77	74	71	69	76	73	71	69	75	72	70	69	67	
			0.56	1.25	80	77	74	72	80	76	74	72	78	76	73	72	77	75	73	71	70
下方投影面積		c m ²	1.5	82	79	77	75	81	78	76	74	80	77	75	74	78	76	75	73	72	
等価発光面積			c m ²	2.0	84	81	79	78	83	81	79	77	81	80	78	77	80	78	77	76	75
取付 高さ	器具間隔最大限		2.5	85	83	81	80	84	82	81	79	83	81	80	79	81	80	79	78	76	
	横方向 (A) 縦方向 (B)		3.0	86	84	83	81	85	83	82	81	83	82	81	80	82	81	80	79	77	
H m	0.36 H m 0.36 H m		4.0	87	85	84	83	86	85	84	83	84	83	82	81	83	82	81	80	78	
			5.0	87	86	85	84	87	86	85	84	85	84	83	82	83	82	82	81	79	
			7.0	88	87	86	86	87	86	86	85	85	85	84	84	84	83	83	82	80	
			10.0	89	88	87	87	88	87	87	86	86	85	85	85	84	84	83	83	81	

