

屋内照明器具特性

| | | |
|---------|--------------------------|----------|
| 品番 (品名) | NTS62002W+NTS90151+NTS91 | |
| 光源 | LED3500_70_925 ×1 | 925.0 lm |
| 管理番号 | K0168007(1)DJ1 | |
| BZ分類 | BZ1 | |

| 器具効率 | 100% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% |
|------|-------------|---------------------|---------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|-----|
| | | | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | |
| 上方光束 | 0% | 壁 | 照明率 (X0.01) | | | | | | | | | | | | | | | | ZCM |
| 下方光束 | 100% | 床 | 照明率 (X0.01) | | | | | | | | | | | | | | | | ZCM |
| 保守率 | 良 中 否 | 0.63 0.6 0.56 | 室指数 | | | | | | | | | | | | | | | | |
| | | | 0.6 | 76 | 68 | 63 | 59 | 75 | 67 | 63 | 59 | 73 | 67 | 62 | 59 | 72 | 66 | 62 | 59 |
| 0.8 | 84 | 77 | 72 | 69 | 83 | 76 | 72 | 69 | 81 | 75 | 71 | 68 | 79 | 75 | 71 | 68 | 67 | | |
| 1.0 | 89 | 83 | 78 | 75 | 88 | 82 | 78 | 75 | 86 | 81 | 77 | 74 | 84 | 80 | 77 | 74 | 72 | | |
| 1.25 | 93 | 88 | 83 | 80 | 92 | 87 | 83 | 80 | 90 | 86 | 82 | 79 | 88 | 84 | 81 | 79 | 77 | | |
| 1.5 | 96 | 91 | 87 | 84 | 95 | 90 | 87 | 84 | 92 | 89 | 86 | 83 | 90 | 87 | 85 | 83 | 81 | | |
| 2.0 | 99 | 95 | 92 | 89 | 98 | 94 | 91 | 89 | 96 | 93 | 90 | 88 | 94 | 91 | 89 | 87 | 85 | | |
| 2.5 | 101 | 98 | 95 | 93 | 100 | 97 | 94 | 92 | 98 | 95 | 93 | 91 | 96 | 94 | 92 | 90 | 88 | | |
| 3.0 | 102 | 99 | 97 | 95 | 101 | 99 | 96 | 94 | 99 | 97 | 95 | 93 | 97 | 95 | 94 | 92 | 90 | | |
| 4.0 | 104 | 102 | 100 | 98 | 103 | 101 | 99 | 97 | 100 | 99 | 97 | 96 | 98 | 97 | 96 | 95 | 92 | | |
| 5.0 | 105 | 103 | 101 | 100 | 104 | 102 | 101 | 99 | 101 | 100 | 99 | 98 | 99 | 98 | 97 | 96 | 94 | | |
| 7.0 | 106 | 105 | 103 | 102 | 105 | 104 | 102 | 101 | 103 | 102 | 101 | 100 | 100 | 100 | 99 | 98 | 96 | | |
| 10.0 | 107 | 106 | 105 | 104 | 106 | 105 | 104 | 103 | 103 | 103 | 102 | 101 | 101 | 101 | 100 | 100 | 97 | | |

