

屋内照明器具特性	
品番 (品名)	NWCF17126 (J YOUJI _ WALL)
光源	LED2700_85_820 ×1 820.0 l m
管理番号	K0194990 (2) DR 1
B Z 分類	BZ10 / 0.9 / BZ9 / 1.4 / BZ10 / 2.3 / BZ9 / 3.5 / BZ1

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	50 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	50 %	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.83	0.6	43	31	22	17	39	28	21	15	32	23	17	12	25	18	13	10	4
	中	0.81	0.8	52	39	30	24	47	36	28	22	38	29	23	18	30	23	18	14	8
	否	0.77	1.0	57	45	36	30	52	41	33	27	43	34	28	23	34	27	22	18	10
			1.25	63	51	43	36	57	47	39	33	47	39	33	28	37	31	26	22	13
下方投影面積		c m ²	1.5	67	56	48	41	61	52	44	38	50	43	37	32	40	34	29	26	15
等価発光面積		c m ²	2.0	73	63	55	49	66	58	51	45	55	48	43	38	44	39	35	31	19
取付高さ	器具間隔最大限		2.5	76	68	61	55	70	63	56	51	58	52	47	43	47	42	38	35	22
	横方向 (A)	縦方向 (B)	3.0	79	72	65	59	73	66	60	55	60	55	50	46	49	45	41	38	25
H m	0.00 H m	1.54 H m	4.0	83	76	71	66	76	71	65	61	64	59	55	52	52	49	45	43	29
			5.0	85	80	75	70	79	74	69	65	66	62	59	55	54	51	48	46	31
			7.0	88	84	80	76	81	78	74	70	69	66	63	60	57	54	52	50	35
			10.0	90	87	84	81	84	81	78	75	71	69	66	64	59	57	55	54	38

