

# 屋内照明器具特性

品番 (品名)	NWCF18125 ( J YOUJI _ CEILING )	
光源	LED5000_85_840 ×1	840.0 l m
管理番号	K0194992 ( 2 ) DR 1	
BZ分類	BZ5	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
上方光束	2 %	床	10 %				10 %				10 %				10 %				0 %				
下方光束	98 %	室指数	照明率 ( X0.01 )																				ZCM
保守率	良	0.83	0.6	5.6	4.4	3.6	3.0	5.5	4.3	3.6	3.0	5.2	4.2	3.5	3.0	5.0	4.1	3.4	3.0	2.8			
	中	0.81	0.8	6.6	5.5	4.7	4.1	6.5	5.4	4.6	4.1	6.2	5.2	4.6	4.0	5.9	5.1	4.5	4.0	3.8			
	否	0.77	1.0	7.3	6.2	5.4	4.9	7.1	6.1	5.4	4.8	6.8	5.9	5.3	4.8	6.5	5.8	5.2	4.7	4.5			
			1.25	7.9	6.9	6.2	5.6	7.7	6.8	6.1	5.6	7.4	6.6	6.0	5.5	7.1	6.4	5.9	5.5	5.2			
下方投影面積		cm <sup>2</sup>	1.5	8.3	7.4	6.7	6.2	8.2	7.3	6.7	6.2	7.8	7.1	6.5	6.1	7.5	6.9	6.4	6.0	5.7			
等価発光面積		cm <sup>2</sup>	2.0	8.9	8.2	7.6	7.0	8.7	8.0	7.5	7.0	8.4	7.8	7.3	6.9	8.1	7.6	7.2	6.8	6.5			
取付高さ	器具間隔最大限		2.5	9.3	8.6	8.1	7.6	9.1	8.5	8.0	7.6	8.7	8.3	7.8	7.4	8.4	8.0	7.7	7.3	7.0			
	横方向 (A)	縦方向 (B)	3.0	9.5	9.0	8.5	8.1	9.3	8.8	8.4	8.0	9.0	8.6	8.2	7.9	8.7	8.3	8.0	7.7	7.4			
H <sub>m</sub>	1.32 H <sub>m</sub>	1.31 H <sub>m</sub>	4.0	9.8	9.4	9.0	8.6	9.7	9.2	8.9	8.6	9.3	9.0	8.7	8.4	9.0	8.7	8.5	8.2	7.9			
			5.0	10.0	9.6	9.3	9.0	9.8	9.5	9.2	8.9	9.5	9.3	9.0	8.8	9.2	9.0	8.8	8.6	8.3			
			7.0	10.2	10.0	9.7	9.5	10.1	9.8	9.6	9.4	9.8	9.6	9.4	9.2	9.5	9.3	9.1	9.0	8.7			
			10.0	10.4	10.2	10.0	9.8	10.2	10.1	9.9	9.7	10.0	9.8	9.7	9.5	9.7	9.6	9.4	9.3	9.0			

