

屋内照明器具特性

品番 (品名)	NWCF18126 (J YOUJI _ CEILING	
光源	LED2700_85_770 ×1	770.0 l m
管理番号	K0195000 (2) DR 1	
B Z 分類	B Z 5	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
上方光束	2 %	床	10 %				10 %				10 %				10 %				0 %				
下方光束	98 %	室指数	照明率 (X0.01)																				Z C M
保守率	良 中 否 0.83 0.81 0.77	0.6	56	44	36	30	55	43	36	30	52	42	35	30	50	41	34	30	28				
		0.8	66	55	47	41	65	54	46	41	62	52	46	40	59	51	45	40	38				
		1.0	73	62	54	49	71	61	54	48	68	59	53	48	65	58	52	47	45				
		1.25	79	69	62	56	77	68	61	56	74	66	60	55	71	64	59	55	52				
下方投影面積	c m ²	1.5	83	74	67	62	82	73	67	62	78	71	65	61	75	69	64	60	57				
		2.0	89	82	76	70	87	80	75	70	84	78	73	69	81	76	72	68	65				
取付高さ	器具間隔最大限		2.5	93	86	81	76	91	85	80	76	87	83	78	74	84	80	77	73				
	横方向 (A)	縦方向 (B)	3.0	95	90	85	81	93	88	84	80	90	86	82	79	87	83	80	77				
H m	1.32 H m	1.31 H m	4.0	98	94	90	86	97	92	89	86	93	90	87	84	90	87	85	82				
			5.0	100	96	93	90	98	95	92	89	95	93	90	88	92	90	88	86				
			7.0	102	100	97	95	101	98	96	94	98	96	94	92	95	93	91	90				
			10.0	104	102	100	98	102	101	99	97	100	98	97	95	97	96	94	93				

