

屋内照明器具特性

品番 (品名)	NWCF18126 (J YOUJI _ WALL)																
光源	LED2700_85_770 ×1 770.0 l m																
管理番号	K0195002 (2) DR 1																
BZ分類	BZ10																

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束	50 %	室指数	照明率 (X0.01)																	ZCM	
下方光束	50 %																				
保守率	良	0.83	0.6	43	30	21	15	39	27	19	14	31	22	16	11	24	17	12	8	3	
	中	0.81	0.8	51	38	29	23	46	34	26	21	37	28	22	17	29	22	17	13	6	
	否	0.77	1.0	57	44	35	28	51	40	32	26	42	33	26	21	33	26	21	17	9	
			1.25	62	50	41	35	57	46	38	32	46	38	31	26	36	30	25	21	11	
下方投影面積	c m ²		1.5	66	55	47	40	60	51	43	36	49	42	35	30	39	33	28	24	14	
等価発光面積	c m ²		2.0	72	62	54	48	66	57	50	44	54	47	42	37	43	38	33	30	18	
取付高さ	器具間隔最大限		2.5	76	67	60	53	69	62	55	49	57	51	46	41	46	41	37	34	21	
	横方向 (A)	縦方向 (B)	3.0	79	71	64	58	72	65	59	54	60	54	49	45	48	44	40	37	24	
H m	0.00 H m	1.85 H m	4.0	82	76	70	65	76	70	65	60	63	59	54	51	51	48	45	42	27	
			5.0	85	79	74	69	78	73	68	64	66	62	58	54	54	50	48	45	30	
			7.0	88	83	79	75	81	77	73	70	68	65	62	59	56	54	51	49	34	
			10.0	90	87	83	80	84	80	77	75	71	68	66	64	59	57	55	53	37	

