

屋内照明器具特性

品番 (品名)	NWCF18508 (J YOUJI _ WALL)																
光源	LED3500_85_490 ×1 490.0 l m																
管理番号	K0195035 (1) DR 1																
BZ分類	BZ10																

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束	50 %	室指数	照明率 (X0.01)																		
下方光束	50 %		ZCM																		
保守率	良 中 否	0.83	0.6	4.2	2.9	2.1	1.5	3.8	2.7	1.9	1.4	3.1	2.2	1.6	1.1	2.4	1.7	1.2	0.8	0.3	
		0.81	0.8	5.1	3.8	2.9	2.2	4.6	3.4	2.6	2.0	3.7	2.8	2.2	1.7	2.9	2.2	1.7	1.3	0.6	
		0.77	1.0	5.6	4.4	3.5	2.8	5.1	4.0	3.2	2.6	4.2	3.3	2.6	2.1	3.3	2.6	2.1	1.6	0.8	
			1.25	6.2	5.0	4.1	3.4	5.6	4.6	3.8	3.2	4.6	3.8	3.1	2.6	3.6	3.0	2.5	2.1	1.1	
下方投影面積			1.5	6.6	5.5	4.6	3.9	6.0	5.0	4.3	3.6	4.9	4.1	3.5	3.0	3.9	3.3	2.8	2.4	1.4	
等価発光面積			2.0	7.2	6.2	5.4	4.7	6.6	5.7	5.0	4.4	5.4	4.7	4.1	3.7	4.3	3.8	3.3	2.9	1.8	
取付高さ	器具間隔最大限		2.5	7.6	6.7	6.0	5.3	6.9	6.2	5.5	4.9	5.7	5.1	4.6	4.1	4.6	4.1	3.7	3.3	2.1	
	横方向 (A)	縦方向 (B)	3.0	7.9	7.1	6.4	5.8	7.2	6.5	5.9	5.4	6.0	5.4	4.9	4.5	4.8	4.4	4.0	3.7	2.4	
H _m	0.00H _m	1.63H _m	4.0	8.2	7.6	7.0	6.5	7.6	7.0	6.5	6.0	6.3	5.8	5.4	5.0	5.1	4.8	4.4	4.1	2.7	
			5.0	8.5	7.9	7.4	6.9	7.8	7.3	6.8	6.4	6.5	6.1	5.8	5.4	5.3	5.0	4.7	4.5	3.0	
			7.0	8.8	8.3	7.9	7.5	8.1	7.7	7.3	7.0	6.8	6.5	6.2	5.9	5.6	5.4	5.1	4.9	3.4	
			10.0	9.0	8.7	8.3	8.0	8.3	8.0	7.7	7.4	7.1	6.8	6.6	6.4	5.9	5.7	5.5	5.3	3.7	

