

屋内照明器具特性	
品番 (品名)	PTSA7520K(1TOUBUN)
光源	LED2000_70_29 x1                      29.0 l m
管理番号	K0176951(0)DY1
BZ分類	BZ5/0.7/BZ4/3.5/BZ5

器具効率	100%	天井	80%				70%				50%				30%				0%			
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
上方光束	4%	床	10%				10%				10%				10%				0%			
下方光束	96%	室指数	照明率 ( X0.01)                      ZCM																			
保守率	良	0.69	0.6	58	46	39	33	57	45	38	33	54	44	38	33	51	43	37	33	30		
	中	0.67	0.8	68	57	49	44	66	56	49	43	63	54	48	43	60	53	47	42	40		
	否	0.63	1.0	74	64	57	51	73	63	56	51	69	61	55	50	66	59	54	49	47		
			1.25	80	71	64	58	78	70	63	58	75	67	62	57	72	65	60	56	54		
下方投影面積		cm <sup>2</sup>	1.5	84	76	69	64	82	74	68	63	79	72	67	62	75	70	65	61	58		
等価発光面積		cm <sup>2</sup>	2.0	89	82	77	72	88	81	76	71	84	78	74	70	81	76	72	69	66		
取付高さ	器具間隔最大限		2.5	93	87	82	77	91	85	81	76	87	83	79	75	84	80	77	74	70		
	横方向 (A)	縦方向 (B)	3.0	95	90	85	81	93	88	84	80	90	86	82	79	86	83	80	77	74		
Hm	1.19Hm	1.18Hm	4.0	98	94	90	87	96	92	89	86	93	90	87	84	90	87	84	82	79		
			5.0	100	96	93	90	98	95	92	89	95	92	90	87	91	89	87	85	82		
			7.0	102	99	97	95	100	98	96	93	97	95	93	91	94	92	91	89	85		
			10.0	104	102	100	98	102	100	98	97	99	97	96	94	96	94	93	92	88		

